EXHIBIT A

LPA RX 851 WD

Page 1 of 4 Rev. 01/21

Ver. Date 02/08/2022 PID 114254

PARCEL 31-WD FRA-161-13.03 ALL RIGHT, TITLE AND INTEREST IN FEE SIMPLE IN THE FOLLOWING DESCRIBED PROPERTY WITHOUT LIMITATION OF EXISTING ACCESS RIGHTS IN THE NAME AND FOR THE USE OF THE CITY OF COLUMBUS, OHIO, A MUNICIPAL CORPORATION

Grantor/Owner, for himself and his heirs, executors, administrators, successors and assigns, reserves all existing rights of ingress and egress to and from any residual area (as used herein, the expression "Grantor/Owner" includes the plural, and words in the masculine include the feminine or neuter).

[Surveyor's description of the premises follows]

Situated in the State of Ohio, County of Franklin, City of Columbus, lying in Quarter Township 4, Township 2 North, Range 18 West, of the United-States Military Lands, and being part of a 18.592 acre tract conveyed to C-K Spring Creek LLC, a Delaware limited liability company (hereinafter referred to as "Grantor") by deed of record in Instrument Number 200110110235193 (Franklin County Parcel Number 010-101716-00) (all documents referenced herein are from the Franklin County Recorder's Office), and being more particularly described as follows:

BEGIN FOR REFERENCE at the intersection of the centerline right-of-way of East Dublin Granville Road (SR 161) (FRA-161-11.57) (width varies), centerline station 690+16.35 and center line of right-of-way of Spring Run Drive (50 feet in width), centerline station 31+47.04, being referenced by a found iron pin in concrete at East Dublin Granville Road (SR 161) centerline station 695+00.18, which bears South 75° 19' 01" East a distance of 483.83 feet;

Thence the following six (6) courses and distances along the centerline of right-of-way of Spring Run Drive;

- 1. North 12° 47' 17" East a distance of 179.63 feet to a 1 inch steel rod at a point of curvature at centerline Station 33+26.67;
- Along a curve to the left with a radius of 225.00 feet, a delta angle of 29° 24' 43", an arc length of 115.50 feet, a chord distance of 114.24 feet, and a chord bearing of North 11° 02' 43" West, to a 1 inch steel rod at a point of reverse curvature at centerline station 34+42.17;

LPA RX 851 WD

- 3. Along on a curve to the right with a radius of 225.00 feet, a delta angle of 29° 24' 45", an arc length of 115.50 feet, a chord distance of 114.24 feet, and a chord bearing of North 11° 02' 42" West, to a 1 inch steel rod at a point of tangency at centerline station 35+57.67;
- 4. North 03° 39' 41" East a distance of 155.91 feet to a 1 inch steel rod at a point of curvature at centerline station 37+13.58;
- 5. Along a curve to the right with a radius of 45.00 feet, a delta angle of 89° 59' 56", an arc length of 70.69 feet, a chord distance of 63.64 feet, and a chord bearing on North 48° 39' 39" East, to a 1 inch steel rod at a point of tangency at centerline station 37+84.26.
- 6. South 86° 20' 23" East a distance of 159.54 feet along the centerline of Fuji Drive (50 feet in width), to a point being the southwesterly corner of the dedicated right-of-way of Fuji Drive as shown in Plat Book 64, Page 13 and Plat Book 62, Page 68, at centerline station 39+43.80;

Thence North 03° 39' 37" East, a distance of 25.00 feet to a point common to the southeasterly corner of the 18.592 acre tract and the south westerly corner of a 0.751 acre tract conveyed to 2350 Fuji LLC. By deed of record in Instrument Number 201706280087776, on the northerly right-of-way line of Fuji Drive deeded to the City of Columbus by deed of record in Official Record 4279, Page I03, 25.00 feet left of centerline station 39+43.80;

Thence North 86° 20' 23" West a distance of 3.85 feet along the southerly line of the 18.592 acre tract and the northerly right-of-way line of Fuji Drive to a 5/8 inch rebar set with cap stamped "DLZ OHIO INC.", 25.00 feet right of centerline station 39+39.95 and the **TRUE POINT OF BEGINNING** of the parcel herein described;

Thence North 86° 20' 23" West a distance of 225.69 feet continuing along the southerly line of the 18.592 acre tract and the northerly right-of-way line of Spring Run Drive/Fuji Drive to a 5/8 inch rebar set with cap stamped "DLZ OHIO INC." on the line common to the 18.592 acre tract and a 0.587 acre tract conveyed to Sabri Salhieh and Nadera Salhieh by deed of record in Instrument Number 201706120078524 and to the northwest corner of Spring Run Drive, deeded to the City of Columbus by deed of record in official record 3961, Page D05, 53.99 feet left of centerline station 37+48.92;

Thence North 03° 39' 41" East a distance of 30.94 feet along the line common to the 18.592 and 0.587 acre tracts, to a 5/8 inch rebar set with cap stamped "DLZ OHIO INC." on the

LPA RX 851 WD

northeasterly corner of said 0.587 acre tract and a southerly corner of the 18.592 acre tract, 77.83 feet left of centerline station 37+56.98;

Thence leaving the line common to the 18.592 acre tract and the 0.587 acre tract the following eight (8) courses across the 18.592 acre tract;

- 1. North 01° 12' 18" East a distance of 22.15 feet to a 5/8 inch rebar set with cap stamped "DLZ OHIO INC.", 97.06 feet left of centerline station 37+60.73;
- 2. South 88° 42' 52" East a distance of 55.27 feet to a 5/8 inch rebar set with cap stamped "DLZ OHIO INC.", 81.34 feet left of centerline station 37+78.65;
- 3. South 01° 17' 08" West a distance of 6.46 feet to a 5/8 inch rebar set with cap stamped "DLZ OHIO INC.", 74.90 feet left of centerline station 37+78.44;
- 4. Along a curve to the left with a radius of 33.00 feet, a delta angle of 58° 00' 32", an arc length of 33.41 feet, a chord bearing of South 27° 43' 08" East with a chord distance of 32.00 feet to a 5/8 inch rebar set with cap stamped "DLZ OHIO INC." a point of tangency, 46.58 feet left of centerline station 37+85.47;
- 5. South 56° 43' 24" East a distance of 23.90 feet to a 5/8 inch rebar set with cap stamped "DLZ OHIO INC." at a point of curvature, 34.77 feet left of centerline station 38+06.25;
- 6. Along a curve to the left with a radius of 48.00 feet, a delta angle of 29° 27' 44", an arc length of 24.68 feet, a chord bearing of South 71° 27' 15" East with a chord distance of 24.41 feet to a 5/8 inch rebar set with cap stamped "DLZ OHIO INC." at a point of tangency, 28.50 feet left of centerline station 38+29.84;
- 7. South 86° 11' 07" East a distance of 44.91 feet to a 5/8 inch rebar set with cap stamped "DLZ OHIO INC.", 28.38 feet left of centerline station 38+74.74;
- 8. South 83° 22' 25" East a distance of 65.29 feet to the **TRUE POINT OF BEGINNING**, containing 0.101 acres, more or less, being subject to all easements, restrictions, and rights-of-way record.

This description was prepared by Robert J. Sands, Ohio Professional Survey Number 8053, and is based on a survey conducted by DLZ Ohio, Inc. in May 2019 under his direct supervision.

The bearings for this description are based on the Ohio State Plane Coordinate System, South Zone, and reference the North American Datum of 1983 and the 2007 adjustment (NAD83(2007)), with the bearing of East Dublin Granville Road (SR 161) being South 75° 19' 01" East.

Where described, iron pins set are 5/8 inch rebar, 30 inches long, with yellow caps stamped "DLZ OHIO INC."

All station and offsets referenced in this description are from the right-of-way centerline of Spring Run Drive as described in the plan known as "IMPROVEMENTS OF SR 161 PHASE 1 / PART 2 SPRING RUN DRIVE / PARKVILLE STREET" on file with the Ohio Department of Transportation and the City of Columbus.

Robert J. Sands,

Professional Surveyor No. 8053

ROBERT

SANDS S-8053

591.7 0.101 aun

4000

(010)

101716

DESCRIPTION VERIFIED CORNELL R. ROBERTSON, P.E., P.S.

DATE: 1 RS 22