

EXHIBIT A

Page 1 of 4

LPA RX 887 T

Rev. 07/09

Ver. Date 09/12/2016

PID 95549

**PARCEL 11-T
ARTERIAL STREET REHABILITATION - POLARIS PARKWAY
TEMPORARY EASEMENT FOR THE PURPOSE OF
PERFORMING THE WORK NECESSARY TO
COMPLETE GRADING AND DRIVEWAY WORK
FOR 24 MONTHS FROM DATE OF ENTRY BY THE
CITY OF COLUMBUS, DELAWARE COUNTY, OHIO**

[Surveyor's description of the premises follows]

Situated in the City of Columbus, County of Delaware, and State of Ohio, being in Farm Lot 18, Quarter Township 4, Township 3 North, Range 18 West of the United States Military District, and being a part of that 1.423 acre tract conveyed to United Dairy Farmers, Inc., an Ohio Corporation, by Official Record 17, Page 428, all references being to the Delaware County Recorder's Office, Delaware County, Ohio, and being bounded and more particularly described as follows:

Being a parcel of land lying on the south side of the centerline of existing right-of-way of Polaris Parkway, as shown and delineated upon the centerline plat with the right-of-way plans designated as Arterial Street Rehabilitation – Polaris Parkway prepared for the City of Columbus, Department of Public Services, by Carpenter Marty Transportation Inc., as recorded in Official Record Volume 1450, Page 927 (made a part hereof by reference), and being more particularly described as follows:

Beginning, for reference, at a 1" iron pipe found with a yellow cap stamped "CIVIL ENGR ASSOC." at a point of tangency in said centerline, said pin being Station 169+55.73 in said centerline;

Thence along said centerline the following two courses:

EXHIBIT A

- 1) North $46^{\circ} 10' 37''$ East a distance of 502.91 feet to a point of curvature in said centerline, said point being Station 174+58.64 in said centerline;
- 2) With a curve to the right having a radius of 1432.39 feet, a central angle of $32^{\circ} 12' 36''$, an arc length of 805.24 feet, a chord bearing North $62^{\circ} 16' 55''$ East, and a chord distance of 794.68 feet to Station 182+63.88 in said centerline;

Thence South $11^{\circ} 36' 48''$ East a distance of 50.00 feet to a 1" iron pipe found in the existing southerly right-of-way line of said Polaris Parkway, said pipe being 50.00 feet right of Station 182+63.88 in said centerline;

Thence along said southerly line South $34^{\circ} 53' 44''$ East a distance of 21.80 feet to an iron pin set at the Grantor's northwesterly corner, said pin being 70.00 feet right of Station 182+72.94 in said centerline, said pin also being the TRUE POINT OF BEGINNING of the parcel herein conveyed;

Thence along the Grantor's northerly line, also being the existing southerly right-of-way line of said Polaris Parkway with a curve to the right having a radius of 1362.39 feet, a central angle of $9^{\circ} 04' 56''$, an arc length of 215.96 feet, a chord bearing of North $83^{\circ} 17' 25''$ East, and a chord distance of 215.73 feet to an iron pin set 70.00 feet right of Station 185+00.00 in said centerline;

Thence along the proposed southerly right-of-way line of said Polaris Parkway the following two courses:

- 1) South $88^{\circ} 12' 00''$ East a distance of 35.60 feet to an iron pin set 72.00 feet right of Station 398+85.62 in said centerline;
- 2) North $89^{\circ} 19' 39''$ East a distance of 80.35 feet to an iron pin set 72.00 feet right of Station 399+65.97 in said centerline;

EXHIBIT A

LPA RX 887 T

Page 3 of 4

Rev. 07/09

Thence along the existing westerly right-of-way line of Olde Worthington Road the following two courses:

- 1) South 43° 12' 23" East a distance of 14.31 feet to a 1" iron pipe found 82.55 feet right of Station 399+75.65 in said centerline;
- 2) With a curve to the right having a radius of 460.00 feet, a central angle of 2° 33' 35", an arc length of 20.55 feet, a chord bearing South 4° 41' 35" West, and a chord distance of 20.55 feet to a point 103.00 feet right of Station 399+73.72 in said centerline;

Thence across said 1.423 acre tract along the proposed temporary southerly right-of-way line of said Polaris Parkway the following five courses:

- 1) North 59° 46' 20" West a distance of 25.31 feet to a point 90.00 feet right of Station 399+52.00 in said centerline;
- 2) North 86° 30' 21" West a distance of 68.82 feet to a point 85.00 feet right of Station 185+35.00 in said centerline;
- 3) South 84° 15' 37" West a distance of 103.38 feet to a point 90.00 feet right of Station 184+25.00 in said centerline;
- 4) North 72° 37' 56" West a distance of 25.55 feet to a point 80.00 feet right of Station 184+00.00 in said centerline;
- 5) South 78° 54' 05" West a distance of 113.23 feet to the Grantor's westerly line, said point being 85.00 feet right of Station 182+79.93 in said centerline;

EXHIBIT A

Page 4 of 4

LPA RX 887 T

Rev. 07/09

Thence along said westerly line North 34° 53' 44" West a distance of 16.39 feet to the TRUE POINT OF BEGINNING, containing 0.123 acres, of which the present road occupies 0.000 acres.

The above described tract is located in Auditor's Parcel Number 318-442-02-027-003.

Grantor claims title by Official Record 17, Page 428, Delaware County Recorder's Office.

This description is based on a survey performed for the City of Columbus in June of 2015 by Carpenter Marty Transportation Inc. This description was prepared and reviewed on August 31, 2016 by Kevin P. Carpenter, Registered Surveyor Number 8124.

The bearings found herein are based on the Ohio State Plane Coordinate System, North Zone, NAD 83 (2011). Bearings shown hereon are based on true north observed by Carpenter Marty Transportation, using a Leica GNSS Viva CS15/GS15 receiver. Based on this the bearing of Interstate 71 is North 3° 32' 22" East.

Monuments referred to as iron pins set are 3/4" x 30" topped by a 2" diameter aluminum cap stamped "CITY OF COLUMBUS R/W, P.S. 8124". Right of way monuments called for as set herein shall be set upon completion of the acquisition process.