



Product Quotation

**Prepared For:
City of Columbus
Columbus Ohio 43215**



**Prepared By:
JAYSON MARSHALL
Hy-Tek JCB
Columbus OH 43217
mobile: (614)-867-7129**

Image is for indicative purpose only and may not represent exact equipment being quoted



Standard Equipment

Standard Equipment and Features & Benefits related to this product are subject to change without notice

GENERAL	One piece unitized mainframe with sway control, stabilizers and componentized driveline
ENGINE	109 HP Tier 4 Final, Dual element air cleaner, spin-on fuel filter, Fuel/water separator, Anti-freeze protection to -30 deg. F.
TRANSMISSION	JCB 4x4 Powershift, Powershuttle direction change, 2.2:1 ratio torque converter, transmission disconnect on loader lever.
AXLES	JCB MAX-TRAC with torque proportioning and outboard planetary drive
BRAKES	Internal mounted, multi-disc, oil immersed, Servo assisted hydraulic actuation, self adjusting. Independent disc type parking brake with brake on alarm and transmission disconnect.
ELECTRICAL	12 volt, Meets IP67 water ingress test standard, 95 amp alternator, 850 CCA low maintenance battery.
INSTRUMENTS	Audible and visual warning system, Tachometer, Hourmeter, Fuel Gauge, Coolant temp. gauge, Warning light for battery charge, air cleaner restriction, engine oil pressure, engine coolant temp., trans oil pressure, parking brake.
CAB UNIT	Meets SAE J231 FOPS/ SAE J1040 ROPS requirements, suspension seat with seat belt, tilt steering column, heater with defroster vent system, windshield wipers and washers for front/rear and roof glass, rear view mirror, front worklights, horn, in-cab storage. Backup alarm meets SAE J994, Operation and part manuals, operation video.
CANOPY UNIT	Meets SAE J231 FOPS/SAE J1040 ROPS requirements, suspension seat with seat belt, tilt steering, rear view mirror, horn, in-cab storage, backup alarm meets SAE J994, operation and parts manuals. Operation video.
TIRES	Choice of Options available (none standard)
TELESCOPIC BOOM	Three section, 44' 3" lift height with hydraulic parallel lift, 10,000 lbs. maximum lift capacity. Boom sections extended by hydraulic cylinders.
CARRIAGE	Choice of Options available (none standard)
HYDRAULICS	Open center system with 29 gpm, single auxiliary hydraulic service.
LIVELINK	2 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control





Features and Benefits

Standard Equipment and Features & Benefits related to this product are subject to change without notice

Rugged tool carrier boom

Boom design and strength, no restriction on bucket use with high bucket breakout force

JCB Q-fit with auxiliary hydraulics

Robust design with easy to operate latching mechanism -
OPTIONAL HYDRAULIC LATCHING

Choice of attachments

Great versatility and higher utilization

Cylinder assisted swing up engine compartment

Easy service and excellent noise reduction

Sway control

Machine leveling on uneven terrain

Low profile, high tensile boom

All around visibility, strength and durability

Nylacast boom wear pads and waxoyl dry film lubricant

Excellent wear characteristics; dry lubricant does not collect abrasives and extends life of wear pads

Three steer modes

Selectable 2ws, 4 ws and crab steer for excellent maneuverability

Optional deluxe cab trim

Unsurpassed visibility and comfort await you

Wheel loader style joystick

Intuitive to operate - translates into immediate productivity





Prepared For:
City of Columbus
77 North Front Street
Columbus Ohio 43215
Fifth Floor
fax:fax:

Dealer Information
Hy-Tek JCB
2222 Rickenbacker Parkway West
Columbus OH 43217
phone:614.497.2500

Prepared By:
JAYSON MARSHALL
jmarshall@hy-tek.net
mobile: (614)-867-7129
Quote Date: 11/30/16
Valid Until: 12/30/16
Quotation Reference: 142002

Model: 550-140

Qty: 1

Equipment Description

550-140, 4WD 4WS, TELESCOPIC HANDLER WITH SWAY CONTROL AND STABILIZERS, 109 HP TIER 4 FINAL
17.5-25 SGL(12 ply) Industrial tread bias ply NO BALLAST
One auxiliary hydraulic service
CAB WITH HEATER, TINTED GLASS, FRONT AND REAR WIPER
Deluxe fabric air suspension seat
48 inch wide Q-Fit carriage with 2-1/4 inch fork shaft (Use L409 Load Guard)
Operators manual - English Language
WORK LIGHTS - FRONT AND REAR - CAB OR CANOPY
ROTATING BEACON. MAGNETIC BASE.
Engine block heater 110-120 volt 850 Watt
CAB DELUXE TRIM. ONLY FOR MANUAL STEER, 2 LEVER TIER 4 FINAL
STEER COLUMN: ADJUSTABLE TILT AND SLIDE. TIER 4 FINAL
AIR CONDITIONING FOR 81KW(109HP) ENGINE OPTIONS ONLY TIER 4 FINAL
2 SPEED FRONT WIPER
Sun blind front windshield and roof
Fire extinguisher
Face level fan
12V POWER SUPPLY SOCKET
Loadguard (Use with Q-Fit carriage)
48 inch x 5 inch x 2 inch pallet forks (2) for 2-1/4 inch fork shaft (UK sourced)- previously 500M801
Front and Rear Roadlights (includes turn signals) - CAB
2.0 CU yd- 96 inch wide GP Bucket
60 Inch X 5 inch X 2 inch pallet Forks
66 Inch Wide Fork Carriage #500Q921
Truss Boom 12 ft. 1400lb capacity
66 inch wide fork carriage #500Q921
72 inch X 5 inch X 2 inch pallet Forks
Four (4.0) ton Crane Hook
1.25 cu. yd Multi Purpose Bucket # 11066
84 inch HD Brush Grapple w/ dual cylinders

Equipment Total 171,495.00

Total Customer Sale Price 171,495.00

Notes: No Sales or Use tax is included.
Must be ordered by 9/9/2016 to insure 2016 price levels.
P.O.'s after 9/9/2016 will be 2017 model year units and subject to a pricing increase.

The above quote supersedes all preceding price quotes.

C

D

