

CARB 2022 COMPLIANCE IS NOT INCLUDED IN PRICE
CALIFORNIA AND OTHER OPT-IN STATES ADD UP TO \$4,500

CHASSIS SPECS

Engine

Cummins 300HP
(2) Alliance 12V Batteries
18.7 CFM Air Compressor
Turbocharged
w/ Internal Safety Valve
Integral Exhaust Brake
115V Block Heater

Transmission

Allison Automatic
w/ PTO Provision
(1) Dash Mounted PTO
Switch w/ Indicator Lamp
Electronic Cruise Control

Front Axle

FAWR: 14,000 lbs
Tires: 315/80R22.5
Aluminum Wheels
Suspension:
Taperleaf/Dual 14,600 lbs
Front Shock Absorbers
Maintenance Free Rubber
Bushings
Ratio 5.57

Rear Axles

DA-RS-21.0-4 Rear Axle
RAWR: 21,000 lbs R-Series
Tires: 11R22.5 14-Ply
Aluminum Disc Rear Wheels
Differential Lock
Suspension:
Multi-Leaf 23,000 lbs.

Fuel Tanks

50 Gal. Aluminum-LH
6 Gallon DEF Tank
Ratio 5.56

Frame & Bumper

Battery Box Frame Mounted
190" Wheelbase
7/16x3-9/16x11-1/8" Steel Frame
3-Piece 14" Chromed Steel Bumper
w/ Collapsible Ends
Front Tow Hooks

Brake & Trailer System

Air Brakes
WABCO 4S/4M ABS
Brake Line Air Dryer
w/ Heater
Steel Air Brake Reservoirs
Air Connections EOF w/ Glad Hands
SAE J560 7-Way Primary Receptacle
Trailer Hand Brake Control Valve

Cab Features:

106" BBC Flat Roof Cab
Conventional, Aluminum
Fiberglass Hood
Single 14" Round Hadley Air Horn
Single Electric Horn
(5) Amber Marker Lights
Dual West Coast Heated Mirrors
Bright Finish
Opal Gray Vinyl Interior
Heater, Defroster, A.C.
Hi-Back Air Ride Driver Seat
Hi-Back Rider Seat
(1) 12V Power Supply In-Dash
Adjustable Tilt/Tele. Steering Column
Driver Instrumentation Display
97 DB Backup Alarm
AM/FM/WB Radio. Aux Input
White Paint



Body & Equipment

168" Line Body w/ Hotstick Shelf, Streetside & Curbside
Compartmentation, and Hotstick Shelf
Master Lock System on Body, Adjustable Shelves w/ Dividers
and/or Material Hooks in Compartments,
Wheel Chock Storage w/ (2) Chocks

EQUIPMENT SPECS

Aerial Specifications

Standard VN-555-MHI Stacked Boom, Articulating, Non-Overcenter, Material Handling
Aerial Device. Provides 55.5 Ft. Platform Height With Standard Pedestal.
Lower Control Valve With Hydraulic Platform-Tilt Valve At Turret
Platform Support Providing 90 Degree Rotation. For Use With Single 1 Or 2-Man Platforms
W/Truguard™
Primary Unitrol Single-Stick Mounted On Curbside Between The Boom And Platform
With Integral Safety Trigger Including An Emergency Stop. For Use With Any Primary
Bucket Configuration. Handle Faces Away From Elbow.
Open Center Hydraulic System
Closed 24x48, 1 Step To Pedestal
Platform Cover, Nylon/Vinyl, 24x48 In.
Platform Capacity Of 700 Lbs. For Single Two-Man Platform And 2000 Lb. Jib Capacity
Continuous Rotation With Controls On Turret
5 Ft. (1.52 M) Jib And Winch With Hydraulic Extension. Includes 75 Feet Of 9/16 Rope
120 Degree Lower Boom Articulation
Standard pedestal (40 inch)
External Bulkhead Reservoir (9.25 In. X 29.5 High In X 37 In. Wide) With A 30 Gallon Capacity,
External Filter, And Sight Level Gauge.
17 Foot Long Subframe (Welded). 5 Foot Longer
Possum Belly Mounting Hardware For Mounting On Top Of Standard Subframe (One Of The
Subframes Above Is Required). Adjust For 6 In. Variance As Pedestal Will Now Sit On Top
Of The Subframe.
Category B 69 KV Including Electrical Test Band On Upper Boom.
Cummins On Demand Chassis Throttle Ctl
Backup Pump For 12v Chassis (Requires 1 Slip Ring)
Required Auto Lift Throttle For Single Platforms (Requires Chassis Throttle Option And
1 Slip Ring)
Standard 12V Start/Stop (Requires 1 Slip Ring)
Collector Ring, 5-Pass
Hydraulic Tool Power Valve For Ground Controls, Including Pressure And Flow Limit
(W/O Quick Disconnects)
Lift Eye On Lower Boom With 2500 Lb. (1125 Kg) Capacity.
Two Full Body Harness And Lanyards (Extra Large) ARC Flash Rated
Universal White Urethane
A-Frame Outriggers For 35-41 Inch Frame Height
A-Frame Outriggers For 35-41 Inch Frame Height.
12/24 Volt Outrigger/Boom Switch Kit (9-20 GPM)
Outrigger Switch Kit For Main Outriggers, Outrigger Switch Kit For Auxiliary Outriggers
Outrigger Valves With Integral Microswitches (Energized When Control Handle Is Activated)
2 Sets. Auto Throttle Disable

888-684-8146 www.customtruck.com

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING
SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions.
Pictures are representative and may not be identical.

PRICE: \$234,966 USD

Ex Works: Kansas City, MO

*Price Is Subject To Change Without Notice And Is Not Guaranteed Due To Fluctuation In Material
Or Component Prices, Including Manufacturer's Surcharges.*

Sample 60 Month Lease Payment: \$3,185 Subject To Approval
For More Details Call Custom Truck Capital (833) CTC-FIN1

QUOTE NUMBER: LE4.8-D_21

EXPIRATION DATE: 9-30-23