



**CURVE TABLE**

① Δ = 25'18"47"  
 R = 1270.00'  
 L = 561.08'  
 Ch. Bearing = N65°02'48"W  
 Ch. Distance = 556.53'

② Δ = 40°37'03"  
 R = 59.62'  
 L = 42.26'  
 Ch. Bearing = N57°31'04"W  
 Ch. Distance = 41.38'

③ Δ = 40°21'19"  
 R = 59.96'  
 L = 42.23'  
 Ch. Bearing = N17°09'44"W  
 Ch. Distance = 41.36'

**LINE TABLE**

① S86°56'52"E 46.13'  
 ② S03°03'08"W 14.89'  
 ③ S86°56'52"E 123.66'  
 ④ S86°56'52"E 6.50'

- Legend**
- PL Property Line
  - R/W Right-of-Way
  - CL Centerline of Right-of-Way
  - Iron Pin Found (IPF) unless otherwise noted
  - Iron Pin Set unless otherwise noted
  - (D)(P) Deed or Plat
  - (M) Measured Value

**E. P. FERRIS AND ASSOCIATES INC.**  
 Consulting Civil Engineers and Surveyors

**CONTACT:**  
 880 KING AVENUE  
 COLUMBUS, OHIO 43212  
 (614) 299-2999  
 (614) 299-2992 (Fax)  
 www.EPFERRIS.com