August 04, 2011

INTERNATIONAL®

Prepared For: City of Columbus Jerry Buckley 109 N Front St. Columbus, OH 43215-2806 (614)000 - 0000 Reference ID: N/A

Presented By: Miami Valley Int'l Trucks Henry W Gantner 11775 Highway Drive Cincinnati OH 45241 -(513)733-8500

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile 2012 7400 SFA 4X2 (SA525)

APPLICATION:

MISSION:

Front Plow with spreader

Requested GVWR: 37000, Calc. GVWR: 37000

Calc. Start / Grade Ability: 29.50% / 2.72% @ 55 MPH Calc. Geared Speed: 72.7 MPH

FUEL ECONOMY: DIMENSION: ENGINE, DIESEL

8.28 MPG @ 55 MPH

Wheelbase: 177.00, CA: 102.00, Axle to Frame: 63.00

(MaxxForce DT) EPA 10: 270 HP @ 2200 RPM, 860 b-ft Torque @ 1300 RPM, 2400 RPM

Governed Speed

TRANSMISSION, AUTOMATIC:

AXLE, FRONT NON-DRIVING

AXLE, REAR, SINGLE:

(Allison 3000 RDS P) 4th Generation Controls, Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy: Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW

& GCW Max.

Omit Item (Clutch & Control)

(Dana Spicer I-140W) Wide Track, I-Beam Type, 14,000-lb Capacity

(Meritor RS-23-160) Single Reduction, 23,000-to Capacity, 200 Wheel Ends, Driver Controlled

Locking Differential Gear Ratio: 6:14

CAB:

TIRE, FRONT:

CLUTCH

TIRE, REAR:

Conventional (2) 12R22 5 G661 HSA (GOODYEAR) 484 rev/mile, load range H, 16 ply (5) 11R22.5 G182 RSD (GOODYEAR) 496 rev/mile, load range H, 16 ply SUSPENSION, RR, SPRING, SINGLE: Vari-Rate; 31,000-lb Capacity, includes 4500-lb Capacity Multileaf Auxiliary

Cab schematic 100GM PAINT:

Location 1, 4015, Dk Lemon Yellow (Prem)

Chassis schematic N/A

August 04, 2011

INTERNATIONAL®

Vehicle Specifications 2012 7400 SFA 4X2 (SA525)

Code	Description	F/R Wt	Tot Wt	<u>List</u> (USA DOLLAR)
SA52500	Base Chassis, Model 7400 SFA 4X2 with 177.00 Wheelbase, 102.00 CA, and 63.00 Axle to Frame.	6777/3995	10772	\$72,112.00
1CAG	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 456.0" (11582mm) Maximum OAL	92/266	358	\$337.00
1LLA	BUMPER, FRONT Steel, Swept Back	0/0	0	\$0.00
•	Includes : BUMPER, FRONT Powder Coated Gray (Argent) Color			
1WEV	WHEELBASE RANGE 146" (370cm) Through and Including 195" (495cm)	0/0	0	\$0.00
1WTU	FRAME ADDITION, FRONT 1" Integral, Increases BBC, BA and CAL Vehicle Dimensions By 1"	4/0	4	\$0,00
2AET	AXLE, FRONT NON-DRIVING {Dana Spicer I-140W} Wide Track, I-Beam Type, 14,000-lb Capacity	81/0	81	\$1,175.00
	Notes : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.			
3ADD	SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 14,000-lb Capacity; With Shock Absorbers	37/0	37	\$129.00
	Includes : SPRING PINS Rubber Bushings, Maintenance-Free			
	Notes : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.			
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications	0/0	0	\$0.00
	Includes : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : DUST SHIELDS, FRONT BRAKE : DUST SHIELDS, REAR BRAKE : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE Bendix On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SLACK ADJUSTERS, FRONT Automatic : SLACK ADJUSTERS, REAR Automatic : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4			
	Notes : Rear Axle is Limited to 23,000-lb GAWR with Code 04091 BRAKE SYSTEM, AIR and Standard Rear Air Cam Brakes Regardless of Axle/Suspension Ordered.			

INT	rer	NΔ	TIN	NΔ	0

<u>Vehicle Specifications</u> 2012 7400 SFA 4X2 (SA525)

				the state of the s
Code	Description	F/R Wt (lbs)	Tot Wt (lbs)	<u>List</u> (USA DOLLAR)
4619	TRAILER CONNECTIONS Four-Wheel, With Hand Control Valve and Tractor Protection Valve, for Straight Truck	2/0	2	\$317.00
4722	DRAIN VALVE {Bendix DV-2} Automatic; With Heater; for Air Tank	1/0	1	\$119.00
	Includes : DRAIN VALVE Mounted in Wet Tank			
4AZA	AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel)	0/0	0	\$0.00
4EBT	AIR DRYER (Bendix AD-IP) With Heater	21/4	25	\$526.00
	Includes : AIR DRYER LOCATION Inside Left Rail, Back of Cab			
4ESX	BRAKE CHAMBERS, FRONT AXLE {Haldex} 20 Sqln	0/0	0	\$0.00
4EVL	BRAKE CHAMBERS, REAR AXLE {Haldex GC3030LHDHO} 30/30 Spring Brake	0/0	0	\$0.00
	Includes : BRAKE CHAMBERS, SPRING (2) Rear Parking; WITH TRUCK BRAKES: All 4x2, 4x4; WITH TRACTOR BRAKES: All 4x2, 4x4; 6x4 & 6x6 with Rear Tandem Axles Less Than 46,000-lb. or GVWR Less Than 54,000-lb.			
4JCJ	BRAKES, FRONT, AIR CAM S-Cam; 16.5" x 5.0"; Includes 20 Sq. In. Long Stroke Brake Chambers	0/0	0	\$265.00
	Notes : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.			÷
4NDB	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake	0/0	0	\$0.00
	Notes The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.			
4SBC	AIR COMPRESSOR (Bendix Tu-Flo 550) 13.2 CFM Capacity	0/0	0	\$0.00
4VGN	AIR TANK Painted Aluminum, With Straight Thread O-Ring Ports	0/0	0	\$432,00
5710	STEERING COLUMN Tilting and Telescoping	10/0	10	\$344.00
5CAL	STEERING WHEEL 2-Spoke, 18" Diam., Black	0/0	0	\$0.00
5PSA	STEERING GEAR (Sheppard M-100) Power	0/0	0	\$0.00
	EXHAUST SYSTEM Single, Horizontal, Aftertreatment Device Frame Mounted Outside Right Rail Under Cab; Includes Vertical Tail Pipe and Guard	5/-18	-13	\$738.00

Includes
: EXHAUST HEIGHT 10' Exhaust Height - Based on Empty
Chassis with Standard Components (+ or - 1" Height)
: MUFFLER/TAIL PIPE GUARD Non-Bright Finish

August 04, 2011

INTERNATIONAL®

Vehicle Specifications 2012 7400 SFA 4X2 (SA525)

		•		
Code	<u>Description</u>	F/R Wt (lbs)	Tot Wt	<u>List</u> (USA DOLLAR)
7SCY	ENGINE COMPRESSION BRAKE for MaxxForce I6 Engines; Electronically Activated	0/0	0	\$1,322.00
7WBA	TAIL PIPE (1) Turnback Type, Bright, for Single Exhaust	0/0	0	\$94.00
7WZY	SWITCH, FOR EXHAUST 2 Position, Lighted & Letching, ON/ OFF Type, Mounted in IP, Inhibits Diesel Particulate Filter Regeneration as Long as Switch is in ON Position	2/0	2	\$31.00
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0	\$0.00
	Includes : BATTERY BOX Steel with Plastic Lid : DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab : FUSES, ELECTRICAL SAE Blade-Type : HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : HEADLIGHTS (2) Sealed Bearn, Round, with Chrome Plated Bezels : HORN, ELECTRIC Single : JUMP START STUD Located on Positive Terminal of Outermost Battery : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : RUNNING LIGHT (2) Daytime, Included With Headlights : STARTER SWITCH Electric, Key Operated : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector : TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted : WIRING, CHASSIS Color Coded and Continuously Numbered			
8518	CIGAR LIGHTER Includes Ash Cup	1/0	1	\$18.00
8718	POWER SOURCE Cigar Type Receptacle without Plug and Cord	1/0	1	\$30.00
8875	BATTERY TERMINALS Sealed	2/0	2	\$51.00
8GHC	ALTERNATOR {Leece-Neville LBP2203H} Brush Type, 12 Volt 160 Amp. Capacity, Pad Mounted	-11/1	-10	\$132.00
8НАВ	BODY BUILDER WIRING Back of Standard Cab at Left Frame or Under Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn	2/0	2	\$63.00
8НАН	ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package With Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket	0/2	2	\$244.00

Vehicle Specifications 2012 7400 SFA 4X2 (SA525)

	•			
Code	Description	<u>F/R Wt</u> (lbs)	Tot Wt	<u>List</u> (USA DOLLAR)
8MKL	BATTERY SYSTEM {International} Maintenance-Free, (3) 12-Volt 1950CCA Total	41/14	55	\$103.00
8NAA	TAIL LIGHT WIRING MODIFIED Includes: Wiring for Standard Lt & Rt Tail Lights; Separate 8.0' of Extra Cable Wiring for Lt & Rt Body Mounted Tail Lights	0/2	2	\$43.00
8RGA	2-WAY RADIO Wiring Effects; Wiring With 20 Amp Fuse Protection, Includes Ignition Wire With 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab	1/0	1	\$54.00
8RJV	RADIO {International} AM/FM Stereo With Weatherband, Clock, Auxiliary Input, Includes Multiple Speakers	3/0	3	\$338.00
	Includes : SPEAKERS IN CAB (2) Dual-Cone with Deluxe Interior : SPEAKERS IN CAB (4) Coaxial with Premium Interior			•
8THJ	AUXILIARY HARNESS 3.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications	2/0	2	\$64.00
8TKK	TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; With 30 Amp Fuse and Relay, Controlled by Ignition Switch	1/0	1	\$79.00
8WCS	BATTERY DISCONNECT SWITCH {Joseph Pollak 51-315} Positive Type, Lever Operated, Cab Mounted	1/0	1	\$148.00
8WLS	TURN SIGNALS, FRONT Dual Face, Amber/Red, Mounted on Top of Fender, Used With Standard Flush Mounted Front Turn Signal, Side Marker Lamps, Parking Lights and Reflectors	3/0	3	\$74.00
8WML	HEADLIGHTS Long Life Halogen; for Two Light System	0/0	0	\$22.00
8WPH	CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade	0/0		\$70.00
8WRB	HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on	0/0	0	\$22.00
8WTK	STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection	0/0	0	\$0.00
8WVP	HORN, AIR (2) Single Tone, Rectangular, Chrome	0/0	0	\$272.00
LWW8	INDICATOR, LOW COOLANT LEVEL With Audible Alarm	1/0	1	\$0.00
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III With Trip Indicators, Replaces All Fuses Except For 5-Amp Fuses	0/0	0	\$0.00
9HBM	GRILLE Stationary, Chrome	0/0	, 0	\$0.00
9WBC	FRONT END Tilting, Fiberglass, With Three Piece Construction; for 2007 & 2010 Emissions	0/0	0	\$0.00
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0	\$0.00
	Includes : PAINT SCHEMATIC ID LETTERS "GM"			
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0	\$0.00
10769	PAINT CLASS Premium Color.	0/0	0	\$210.00

<u>Vehicle Specifications</u> 2012 7400 SFA 4X2 (SA525)

	scription UTCH Omit Item (Clutch & Control)	F/R Wt (lbs)		<u>List</u> (USA DOLLAR)
11001 CL	UTCH Omit Item (Clutch & Control)	001.46		,
		-63/-12	-75	\$0.00
	O EFFECTS, ENGINE FRONT Less PTO Unit, Includes apter Plate on Engine Front Mounted	10/0	10	\$87.00
RP	IGINE, DIESEL {MaxxForce DT} EPA 10, 270 HP @ 2200 M, 860 lb-ft Torque @ 1300 RPM, 2400 RPM Governed eed	0/0	0	\$0.00
: AI (Air : AI Deg : Ci Hea : CI	ludes IR COMPRESSOR AIR SUPPLY LINE Naturally-Aspirated r Brake Chassis Only) NTI-FREEZE Red Shell Rotella Extended Life Coolant; -40 grees F/ -40 Degrees C; for MaxxForce Engines OLD STARTING EQUIPMENT Intake Manifold Electric Grid ater with Engine ECM Control RUISE CONTROL Electronic; Controls Integral to Steering			
: Ei : Ei : FU : FU Filte Moi : GO : OI	NGINE OIL DRAIN PLUG Magnetic NGINE SHUTDOWN Electric, Key Operated UEL FILTER Included with Fuel/Water Separator UEL/WATER SEPARATOR Fuel/Water Separator and Fuel er in a Single Assembly; With Water-in-Fuel Sensor; Engine unted OVERNOR Electronic IL FILTER, ENGINE Spin-On Type //ET TYPE CYLINDER SLEEVES			
	N DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed h Residual Torque Device for Disengaged Fan Speed	9/0	9	\$274.00
	ludes AN Nylon		,	
Cor	DIATOR Aluminum, Cross Flow, Series System; 1228 SqIn re and 648 SqIn Charge Air Cooler and 342 SqIn Low nperature Radiator	-7/2	-5	\$0.00
: DE : HC The	udes EAERATION SYSTEM with Surge Tank DSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; ermoplastic Coolant Hose Clamps ADIATOR HOSES Premium, Rubber			
12UXG FEE	DERAL EMISSIONS for 2010; MaxxForce DT Engines	0/0	0	\$6,000.00
	CLEANER Single Element, with Integral Snow Valve and In- Control	2/0	2	\$157.00
	<u>udes</u> AUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted			
Elec	ROTTLE, HAND CONTROL Engine Speed Control; ctronic, Stationary, Variable Speed; Mounted on Steering eei	0/0	0	\$0.00
Inclu With	GINE CONTROL, REMOTE MOUNTED Provision for; udes Wiring for Body Builder Installation of PTO Controls; n Ignition Switch Control for MaxxForce post 2007 Emissions ctronic Engines	0/0	0	\$45.00

<u>Vehicle Specifications</u> 2012 7400 SFA 4X2 (SA525)

Code	<u>Description</u>	F/R Wt (lbs)	Tot Wt (lbs)	<u>List</u> (USA DOLLAR)
12WTH	BLOCK HEATER, ENGINE {Phillips} 120 Volt/1250 Watt; With "Y" Cord From Socket in Standard Location, For a Dealer Installed Oil Pan Heater, With Extended Life Coated Metal/Plastic/Metal Material Oil Pan, for I6	4/0	4	\$82.00
	Includes : BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door			
	Notes : MPM material is single sheet composite with two layers of sheet metal sandwiching plastic material. MPM material has electrodeposition prime coat with powder coating for the final finish coat.			
12WZE	EMISSION COMPLIANCE Federal, Does Not Comply With California Clean Air Regulations	0/0	0	\$0.00
13AMB	TRANSMISSION, AUTOMATIC {Allison 3000_RDS_P} 4th Generation Controls; Close Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.	195/57	252	\$6,917.00
	Includes : OIL FILTER, TRANSMISSION Mounted on Transmission : TRANSMISSION OIL PAN Magnet in Oil Pan	·		
13WAW	OIL COOLER, AUTO TRANSMISSION (Modine) Water to Oil, for Allison or CEEMAT Transmission	25/0	25	\$667.00
13WBN	TRANSMISSION SHIFT CONTROL (Ailison) T-Bar Type; for Allison 3000 & 4000 Transmission	0/0	. 0	\$371.00
13WLP	TRANSMISSION OIL Synthetic; 29 thru 42 Pints	0/0	0	\$203.00
13WUC	ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction	0/0	0	\$0.00
13WYH	TRANSMISSION TCM LOCATION Located Inside Cab	0/0	0	\$141.00
13WYL	SHIFT CONTROL PARAMETERS Allison Performance Programming in Primary and Allison Economy Programming in Secondary	0/0	0	\$0.00
14ARB	AXLE, REAR, SINGLE {Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, 200 Wheel Ends, Driver Controlled Locking Differential . Gear Ratio: 6.14	0/241	241	\$1,809.00
•	<u>Includes</u> : REAR AXLE DRAIN PLUG (1) Magnetic, For Single Rear Axle			
	Notes : The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear, Special Rating, GAWR; Wheels; Tires. : When Specifying Axle Ratio, Check Performance Guidelines and TCAPE for Startability and Performance			. •
14SAL	SUSPENSION, RR, SPRING, SINGLE Vari-Rate; 31,000-lb Capacity, Includes 4500-lb Capacity Multileaf Auxiliary	0/88	88	\$305.00
	Notes			

Vehicle Specifications 2012 7400 SFA 4X2 (SA525)

<u>Code</u>	Description	F/R Wt (lbs)		<u>List</u> (USA DOLLAR)
•	: The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.	(ibo)	(100)	(compositive)
15LKG	FUEL/WATER SEPARATOR With Thermostatic Fuel Temperature Controlled Electric Heater, and Filter Restriction/ Change Indicator, Includes Standard Equipment Water-in-Fuel Sensor	.5/0	5	\$64.00
15SGG	FUEL TANK Top Draw; D Style, Non Polished Aluminum, 19" Deep, 70 U.S. Gal., 265 L Capacity, With Quick Connect Outlet, Mounted Left Side, Under Cab	-32/-14	-46	\$185.00
16030	CAB Conventional .	0/0	0	\$0.00
	Includes : ARM REST (2) Molded Plastic; One Each Door : CLEARANCE/MARKER LIGHTS (5) Flush Mounted : COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window : CUP HOLDERS Two Cup Holders, Located in Lower Center of Instrument Panel : DOME LIGHT, CAB Rectangular, Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Console, Center Mounted : GLASS, ALL WINDOWS Tinted : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side : GRAB HANDLE, CAB INTERIOR (2) Front of "B" Pillar Mounted, One Each Side : INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color : STEP (4) Two Steps Per Door			
16НВА	GAUGE CLUSTER English With English Electronic Speedometer Includes : GAUGE CLUSTER (6) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic), Tachometer (Electronic), Voltmeter, Washer Fluid Level : ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout : WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage (Visual and Audible)	0/0	о	\$0.00
16HGH	GAUGE, OIL TEMP, ALLISON TRAN	1/0	1	\$48.00
16HHE	GAUGE, AIR CLEANER RESTRICTION (Filter-Minder) With Black Bezel Mounted in Instrument Panel	2/0	2	\$30.00
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0	\$0.00
16JNV	SEAT, DRIVER (National 2000) Air Suspension, High Back With Integral Headrest, Cloth, Isolator, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, -3 to +14 Degree Back Angle Adjust Includes	27/12	39	\$232.00
	: SEAT BELT 3-Point, Lap and Shoulder Belt Type			

Vehicle Specifications 2012 7400 SFA 4X2 (SA525)

August 04, 2011

	2012 7400 SFA 4AZ (SAS2S)			
Code	Description	F/R Wt (lbs)	Tot Wt	<u>List</u> (USA DOLLAR)
16PHX	SEAT, PASSENGER (Gra-Mag) Non Suspension, High Back, Fixed Back, Integral Headrest, Cloth	0/0	0	\$43.00
	Includes : SEAT BELT 3-Point, Lap and Shoulder Belt Type	•		
16SDG	MIRROR, CONVEX, LOOK DOWN (Lang Mekra) Right Side; 6" x 10 1/4", With Bright Finish	2/0	2	\$57.00
16SDU	MIRRORS (2) {Lang Mekra} Styled; Rectangular, 7.09" x 15.75" & Integral Convex Both Sides, 102" Inside Spacing, Breakaway Type, Heated Heads Thermostatically Controlled, Power Both Sides, Clearance Lights LED, Bright Finish Heads & Brackets	8/0	8	\$443.00
16SEE	GRAB HANDLE Chrome; Towel Bar Type With Anti-Slip Rubber Inserts; for Cab Entry Mounted Left Side Only at "B" Pillar	3/0	3	\$118.00
16VCC	SEAT BELT All Orange; 1 to 3	0/0	0	\$26.00
16VSL	WINDSHIELD Heated, Single Piece	0/0	0	\$632.00
16WBY	ARM REST, RIGHT, DRIVER SEAT	3/0	3	\$39.00
16WCT	AIR CONDITIONER (Blend-Air) With Integral Heater & Defroster	40/7	47	\$823.00
	Includes : HEATER HOSES Premium : HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps : REFRIGERANT Hydrofluorocarbon HFC-134A			
16WJS	INSTRUMENT PANEL Center Section, Flat Panel	0/0	. 0	\$0.00
16WJU	WINDOW, POWER (2) And Power Door Locks, Left and Right Doors, Includes Express Down Feature	5/0	5	\$367.00
16WKY	HVAC FRESH AIR FILTER	0/0	0	\$0.00
16WRZ	CAB INTERIOR TRIM Premium	0/0	0	\$304.00
	Includes : "A" PILLAR COVER Molded Plastic : CAB INTERIOR TRIM PANELS Cloth Covered Molded Plastic, Full Height; All Exposed Interior Sheet Metal is Covered Except for the Following: with a Two-Man Passenger Seat or with a Full Bench Seat the Back Panel is Completely Void of Covering : CAB SOUND INSULATION Includes Dash and Engine Cover Insulators : CAB, INTERIOR TRIM, CLOSEOUT Lower Dash Closeout		·	

: CAB, INTERIOR TRIM, CLOSEOUT Lower Dash Closeout Panel; Molded Plastic; Under Instrument Panel Driver Side : CONSOLE, OVERHEAD Molded Plastic; With Dual Storage

Pockets with Retainer Nets, CB Radio Pocket, Speakers, and Reading Lights

: COURTESY LIGHT (2) Mounted in Front Map Pocket Left and Right Side

: DOOR TRIM PANELS with Cloth Insert on Bolster Driver and Passenger Doors

: FLOOR COVERING Rubber, Black : GAUGE, TEMPERATURE, AMBIENT Includes Compass Readout and Wiring and Sensor With Display Unit Mounted in Cluster

: HEADLINER Soft Padded Cloth

<u>Vehicle Specifications</u> 2012 7400 SFA 4X2 (SA525)

Code	Description	F/R Wt (lbs)	Tot Wt	<u>List</u> (USA DOLLAR)
	: INSTRUMENT PANEL TRIM Molded Plastic with Black Center Section : STORAGE POCKET, DOOR (2) Molded Plastic (Carpet Texture), Full-Length; Driver and Passenger Doors : SUN VISOR (3) Padded Vinyl: 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Vanity Mirror and Toll Ticket Strap, plus 1 Auxiliary Visor (Front Only), Driver Side	(100)	(100)	CONTROLENTY
16WSK	CAB REAR SUSPENSION Air Bag Type	0/0	0	\$0.00
16XWD	SUNSHADE, EXTERIOR Aerodynamic, Painted Roof Color; Includes Integral Clearance/Marker Lights	14/3	17	\$203.00
16XWJ	WINDSHIELD WIPER BLADES Snow Type	2/0	2	\$26.00
16XXC	COWL TRAY LID	7/4	11	\$200.00
26DRB	WHEEL, SPARE, DISC 22.5" Non-Polished Aluminum, 10 Stud (285.75MM BC Hub Piloted) 8.25 DC Rim	27/27	54	\$379.00
27DMB	WHEELS, FRONT DISC; 22.5" Non-Polished Aluminum, 10- Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs	-58/0	-58	\$514.00
	Notes : Aluminum Wheels not Painted or Coated : Compatible Tire Sizes: 11R22.5, 12R22.5, 255/70R22.5, 255/80R22.5, 265/75R22.5, 275/70R22.5, 275/80R22.5, 295/75R22.5, 295/80R22.5			
28DMB	WHEELS, REAR DUAL DISC; 22.5" Non-Polished Aluminum, 10-Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs	0/-140	-140	\$1,040.00
	Notes : Aluminum Wheels not Painted or Coated : Compatible Tire Sizes: 11R22.5, 12R22.5, 255/70R22.5, 255/80R22.5, 265/75R22.5, 275/70R22.5, 275/80R22.5, 295/75R22.5, 295/80R22,5	·		
29007	TIRE, SPARE Equal to Model Standard	45/46	91	\$536.00
	Notes NOTE: Only One Spare Tire per Truck Ordered. Order Must Reflect Number of Tires Required (Including Spare). 10-Digit Tire Code and Spare Rim/Wheel Code Must be Specified.			
60AAG	BDY INTG, REMOTE POWER MODULE Mounted Inside Cab behind Driver Seat; Up to 6 Outputs & 6 Inputs, Max. 20 amp. per Channel, Max. 80 amp Total (Includes 1 Switch Pack With Latched Switches)	0/0	0	\$531.00
7382130121	(5) TIRE, REAR 11R22.5 G182 RSD (GOODYEAR) 496 rev/mile, load range H, 16 ply	0/110	110	\$855.00
7382158107	(2) TIRE, FRONT 12R22.5 G661 HSA (GOODYEAR) 484 rev/mile, load range H, 16 ply	38/0	38	\$548.00
	Total of Product Features			\$105,279.00
	Cab schematic 100GM			

Vehicle Specifications 2012 7400 SFA 4X2 (SA525)

August 04, 2011

Code

Description

F/R Wt Tot Wt

<u>List</u>

Location 1: 4015, Dk Lemon Yellow (Prem)

(lbs)

(USA DOLLAR)

Chassis schematic N/A

Total Component Weight:

7394/4697

12091

(lbs)

Total List Price Including Options:

\$105,279.00

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.

ENGINE, DIESEL (0012NUR) ATTACHMENTS: 0004619 (TRAILER CONNECTIONS)

<u>Parameter</u>	<u>Value</u>	<u>UOM</u>
Max Vehicle Speed:7902	72	MPH
Max Eng Speed w/Speed Fault:7901	2400	N/A
IDLE Shutdown Timer Mode:7400	OFF	N/A
IDLE Shutdown Time:7401	5	MIN
ISD - Max Intake Air Temp:7402	44	· C
Cruise Control - MIN Veh SP:7603	35	MPH
Cruise Control - MAX Speed:7604	72	MPH
Retarder Mode	COM-LTCH	N/A
Service Interval - Enable:9500	OFF	N/A
Service Interval - Distance:9503	12000	MILES
Service Interval - Run Time:9502	450.0	HOURS
Service Interval - Fuel Used:9501	1500	GALLONS
PTO - Max Vehicle Speed:7501	5	MPH
PTO - Vehicle Speed Override:7518	AFFCTRPS:	N/A
PTO - Max Engine Speed:7508	2200	RPM
PTO - Ramp Rate:7507	100	RPM/SEC
PTO - Driveline Mode:9301	NEUTRLOP	N/A
Remote Pedal - Enable:7504	NO	N/A
Remote Pedal - Return To 0 Req:7513	RTZ-NOT	N/A
Remote Pedal - IN-CAB override:7523	AFFCTRPS	N/A
Remote Pedal - Driveline OVRD:7522	AFFCTRPS	N/A
Customer Password:8700	0000	N/A

These Electronic Parameters have been successfully finalized

Financial Summary 2012 7400 SFA 4X2 (SA525)

August 04, 2011

(USA DOLLAR)

<u>Description</u>		<u>Price</u>
Factory List Prices:		r.
Product Items	\$105,279.00	
Service Items	\$0.00	•
Total Factory List Price Including Options:		\$105,279.00
Gledhill Snow Plow Hitch	\$4,532.00	
Diagnostic & trouble shooting	\$500.00	
mechanics training; Full tank Fuel -		
Center City	• •	
Install safety Equip CCI	\$195.00	
P & D Center City	\$0.00	
Total Preparation And Delivery:		\$5,227.00
Freight Charge	\$1,775.00	
Total Freight:		\$1,775.00
Total Factory List Price Including Freight:	•	\$112,281.00
Less Customer Allowance:		(\$32,613.00)
Total Vehicle Price:		\$79,668.00
Total Warranty:		\$4,209.00
Total Sale Price:		\$83,877.00
Total Per Vehicle Sales Price:		\$83,877.00
Net Sales Price:		\$83,877.00

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:	Accepted by Purchaser
Official Title and Date	Firm or Business Name
Authorized Signature	Authorized Signature and Date
This proposal is not binding upon the seller without Seller's Authorized Signature	
	Official Title and Date

<u>Warranty</u> 2012 7400 SFA 4X2 (SA525)

August 04, 2011

(USA DOLLAR)

Description

<u>Price</u> 4209,00

84 - Month 100,000 mile extended warranty contract 213568 6240. list 3120 net 213267 2178 list 1089 net

Total Warranty: \$4,209.00

Prepared For: City of Columbus John King 109 N Front St. Columbus, OH 43215-2806 (614)000 - 0000 Reference ID: N/A Presented By: Miami Valley Int'l Trucks Henry W Gantner 11775 Highway Drive Cincinnati OH 45241 -(513)733-8500

Thank you for the opportunity to provide you with the following quotation on a new international truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile 2012 7400 SFA 6X4 (SF525)

APPLICATION: MISSION:

FUEL ECONOMY:

DIMENSION: ENGINE, DIESEL:

TRANSMISSION, AUTOMATIC

AXLE, FRONT NON-DRIVING: AXLE, REAR, TANDEM:

CAB: TIRE, FRONT: TIRE, REAR:

SUSPENSION, REAR, TANDEM:

FRAME REINFORCEMENT:

PAINT:

Front Plow with spreader.

Requested GVWR: 58000, Calc. GVWR: 58000.... Calc. Start / Grade Ability: 19:50% £1:90% @ 55 MPH

Calc. Geared Speed: 60.6 MPH

5.92 MPG @ 55 MPH

Wheelbase: 219.00, CA: 144.00, Axle to Frame: 75.00

(MaxxForce 9) EPA 10, 315 HP @ 2000 RPM, 950 lb-ft Torque @ 1200 RPM, 2200 RPM

Governed Speed

(Allison 3000_RDS_P) 4th Generation Controls; Close Ratio, 5-Speed, With Overdrive; On/Off/ Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW

Omit Item (Clutch & Control)

(Mentor MFS-18-133A) Wide Track, I-Beam Type, 18,000-lb Capacity

Meritor MT-40-14X-4DER-P) Single Reduction; 0.433"(11mm) Wall Housing Thickness, 40,000lb Capacity R Wheel Ends, Driver Controlled Locking Differential in Rear-Rear Axle, Lube Oil Pump Gear Ratio: 5:86

Conventional

(3) 815/80R22.5 G287 MSA (GOODYEAR) 485 rev/mile, load range L, 20 ply (8) 11R22.5 G182 RSD (GOODYEAR) 496 rev/mile, load range H, 16 ply

(Hendrickson HMX-400-52) Walking Beam Type 52" Axle Spacing; 40,000-lb Capacity, With

Rubber End Bushings, Transverse Torque Rods, Less Shock Absorbers

Outer "C" Channel, Heat Treated Alloy Steel (120,000 PSI Yield); 10.813" x 3.892" x 0.312";

(274.6mm x 98.9mm x 8.9mm); 480.6" (12192mm) Maximum OAL

Cab schematic 100GM

Location 1: 4015, Dk Lemon Yellow (Prem)

Chassis schematic N/A

<u>Vehicle Specifications</u> 2012 7400 SFA 6X4 (SF525)

Code	Description	F/R Wt (lbs)	Tot Wt	<u>List</u> (USA DOLLAR)
SF52500	Base Chassis, Model 7400 SFA 6X4 with 219.00 Wheelbase, 144.00 CA, and 75.00 Axle to Frame.	7342/7074	14416	\$81,168.00
1CBU	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 480.0" (12192) Maximum OAL	100/147	247	\$0.00
1GBP	FRAME REINFORCEMENT Outer "C" Channel, Heat Treated Alloy Steel (120,000 PSI Yield); 10.813" x 3.892" x 0.312"; (274.6mm x 98.9mm x 8.0mm); 480.0" (12192mm) Maximum OAL	409/614	1023	\$1,650.00
1LLA	BUMPER, FRONT Steel, Swept Back	0/0	0	\$0.00
	Includes : BUMPER, FRONT Powder Coated Gray (Argent) Color			
1WDT	FRAME EXTENSION, FRONT Integral; 20" In Front of Grille, With Outer "C" Channel Reinforcement	162/-16	146	\$445.00
1WGB	WHEELBASE RANGE 177" (450cm) Through and Including 226" (575cm)	0/0	0	\$506.00
2ARZ	AXLE, FRONT NON-DRIVING (Meritor MFS-18-133A) Wide Track, I-Beam Type, 18,000-ib Capacity	130/0	130	\$2,088.00
	Notes : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.			
3770	SPRINGS, FRONT AUXILIARY Rubber	10/0	10	\$104.00
3ACR	SUSPENSION, FRONT, SPRING Multileaf, Shackle Type; 18,000-ib Capacity; Less Shock Absorbers	175/0	175	\$79.00
	Includes : SPRING PINS Rubber Bushings, Maintenance-Free	,		•
	Notes : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.			
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications	0/0	0	\$0.00
	Includes : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : DUST SHIELDS, FRONT BRAKE : DUST SHIELDS, REAR BRAKE : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE Bendix On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SLACK ADJUSTERS, FRONT Automatic : SLACK ADJUSTERS, REAR Automatic			

<u>Vehicle Specifications</u> 2012 7400 SFA 6X4 (SF525)

<u>Code</u>	Description	F/R Wt (lbs)	Tot Wt	<u>List</u> (USA DOLLAR)
	: SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4	(IDG)	(103)	(OUT DOLD III)
	Notes : Rear Axle is Limited to 46,000-lb GAWR with Code 04091 BRAKE SYSTEM, AIR and Standard Rear Air Cam Brakes Regardless of Axle /Suspension Ordered.			
4193	BRAKES, FRONT, AIR CAM 16.5" x 6", Includes 24 Sqln Long Stroke Brake Chambers	-62/0	-62	\$0.00
	Notes : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.			
4619	TRAILER CONNECTIONS Four-Wheel, With Hand Control Valve and Tractor Protection Valve, for Straight Truck	2/0	. 2	\$317.00
4722	DRAIN VALVE {Bendix DV-2} Automatic; With Heater; for Air Tank	1/0	1	\$119,00
	Includes : DRAIN VALVE Mounted in Wet Tank			
4AZA	AIR BRAKE ABS (Bendix AntiLock Brake System) Full Vehicle Wheel Control System (4-Channel)	0/0	0	\$0.00
4EBT	AIR DRYER {Bendix AD-IP} With Heater	22/3	25	\$526.00
	Includes : AIR DRYER LOCATION Inside Left Rail, Back of Cab			
4ETE	BRAKE CHAMBERS, FRONT AXLE {Haldex} 24 Sqin	4/0	4	\$13.00
4EVL	BRAKE CHAMBERS, REAR AXLE {Haldex GC3030LHDHO} 30/30 Spring Brake	0/0	0	\$0.00
	Includes : BRAKE CHAMBERS, SPRING (2) Rear Parking; WITHTRUCK BRAKES: All 4x2, 4x4; WITH TRACTOR BRAKES: All 4x2, 4x4; 6x4 & 6x6 with Rear Tandem Axles Less Than 46,000-lb. or GWR Less Than 54,000-lb. : BRAKE CHAMBERS, SPRING (4) Rear Parking; WITHTRUCK BRAKES: All 6x4, 6x6; WITH TRACTOR BRAKES: 6x4 & 6x6 with Rear Tandem Axles 46,000-lb. or Greater or GWR of 54,000-lb. or Greater			
4NDB	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake	0/0	0	\$0.00
	Notes : The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.			
4SBC	AIR COMPRESSOR {Bendix Tu-Flo 550} 13.2 CFM Capacity	0/0	0	\$0.00
4VGN	AIR TANK Painted Aluminum, With Straight Thread O-Ring Ports	-13/-3	-16	\$432.00
5710	STEERING COLUMN Tilting and Telescoping	10/0	10	\$344.00

Vehicle Specifications 2012 7400 SFA 6X4 (SF525)

Code	Description	F/R Wt (lbs)	Tot Wt (lbs)	<u>List</u> (USA DOLLAR)
5CAL	STEERING WHEEL 2-Spoke, 18" Diam., Black	0/0	Ó	\$0.00
5PTB	STEERING GEAR (2) {Sheppard M-100/M-80} Dual Power	119/0	119	\$0.00
7BEJ	EXHAUST SYSTEM Single, Horizontal, Aftertreatment Device Frame Mounted Outside Right Rail Under Cab; Includes Vertical Tail Pipe and Guard	1/-14	-13	\$738.00
	Includes : EXHAUST HEIGHT 10' Exhaust Height - Based on Empty Chassis with Standard Components (+ or - 1" Height) : MUFFLER/TAIL PIPE GUARD Non-Bright Finish			
7SCY	ENGINE COMPRESSION BRAKE for MaxxForce I6 Engines; Electronically Activated	0/0	0	\$1,322.00
7WBA	TAIL PIPE (1) Tumback Type, Bright, for Single Exhaust	0/0	0	\$94.00
7WZY	SWITCH, FOR EXHAUST 2 Position, Lighted & Latching, ON/ OFF Type, Mounted in IP, Inhibits Diesel Particulate Filter Regeneration as Long as Switch is in ON Position	. 2/0	2	\$31.00
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0	\$0.00
	Includes : BATTERY BOX Steel with Plastic Lid : DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab : FUSES, ELECTRICAL SAE Blade-Type : HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : HEADLIGHTS (2) Sealed Beam, Round, with Chrome Plated Bezels : HORN, ELECTRIC Single : JUMP START STUD Located on Positive Terminal of Outermost Battery : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : RUNNING LIGHT (2) Daytime, Included With Headlights : STARTER SWITCH Electric, Key Operated : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector : TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted			
8518	CIGAR LIGHTER Includes Ash Cup	1/0	1	\$18.00
8718	POWER SOURCE Cigar Type Receptacle without Plug and Cord	1/0	1	\$30.00
8875	BATTERY TERMINALS Sealed	2/0	2	\$51.00

<u>Vehicle Specifications</u> 2012 7400 SFA 6X4 (SF525)

Code	Description	<u>F/R Wt</u> (lbs)	Tot Wt (lbs)	<u>List</u> (USA DOLLAR)
8GHC	ALTERNATOR {Leece-Neville LBP2203H} Brush Type, 12 Volt 160 Amp. Capacity, Pad Mounted	-7/-1	-8	\$132.00
8HAB	BODY BUILDER WIRING Back of Standard Cab at Left Frame or Under Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn	2/0	2	\$63.00
8НАН	ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package With Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket	0/2	2	\$244.00
8MKL	BATTERY SYSTEM {International} Maintenance-Free, (3) 12-Volt 1950CCA Total	43/12	55	\$103.00
8NAA	TAIL LIGHT WIRING MODIFIED Includes: Wiring for Standard Lt & Rt Tail Lights; Separate 8.0' of Extra Cable Wiring for Lt & Rt Body Mounted Tail Lights	0/2	2	\$43.00
8RGA	2-WAY RADIO Wiring Effects; Wiring With 20 Amp Fuse Protection, Includes Ignition Wire With 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab	. 1/0	1	\$54.00
8RJV	RADIO (International) AM/FM Stereo With Weatherband, Clock, Auxiliary Input, Includes Multiple Speakers	3/0	3	\$338.00
	includes : SPEAKERS IN CAB (2) Dual-Cone with Deluxe Interior : SPEAKERS IN CAB (4) Coaxial with Premium Interior	•		
8ТНЈ	AUXILIARY HARNESS 3.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications	2/0	2	\$64.00
8ТКК	TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; With 30 Amp Fuse and Relay, Controlled by Ignition Switch	1/0	1	\$79.00
8WCL	HORN, AIR Black, Single Trumpet, Air Solenoid Operated	0/0	0	\$0.00
8WCS	BATTERY DISCONNECT SWITCH (Joseph Pollak 51-315) Positive Type, Lever Operated, Cab Mounted	1/0	1	\$148.00
8WLS	TURN SIGNALS, FRONT Dual Face, Amber/Red, Mounted on Top of Fender, Used With Standard Flush Mounted Front Turn Signal, Side Marker Lamps, Parking Lights and Reflectors	_ 3/0	3	\$74.00
8WML	HEADLIGHTS Long Life Halogen; for Two Light System	0/0	0	\$22.00
8WPH	CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade	0/0	0	\$70.00
8WRB	HEADLIGHTS ON WWIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on	0/0	0	\$22.00
8WTK	STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection	0/0	. 0	\$0.00
8VVVJ	INDICATOR, LOW COOLANT LEVEL With Audible Alarm	1/0	1	\$0.00

Vehicle Specifications 2012 7400 SFA 6X4 (SF525)

<u>Code</u>	Description	F/R Wt	Tot Wt	<u>List</u>
HAX8	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III With Trip Indicators, Replaces All Fuses Except For 5-Amp Fuses	(lbs) 0/0	(lbs) 0	(USA DOLLAR) \$0.00
9 НВМ	GRILLE Stationary, Chrome	0/0	0	\$0.00
9WAC	BUG SCREEN Front End; Mounted Behind Grille	5/0	5	\$131.00
9WBC	FRONT END Tilting, Fiberglass, With Three Piece Construction; for 2007 & 2010 Emissions	-0/0	0	\$0.00
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0	\$0.00
· .	Includes ; PAINT SCHEMATIC ID LETTERS "GM"			
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	. 0	\$0.00
10769	PAINT CLASS Premium Color.	0/0	. 0	\$210.00
11001	CLUTCH Omit Item (Clutch & Control)	-60/-15	-75	\$0.00
12712	OIL FILTER, ENGINE {Hudgins Model 960 Spinner}	25/0	25	\$0.00
12851	PTO EFFECTS, ENGINE FRONT Less PTO Unit, Includes Adapter Plate on Engine Front Mounted	10/0	10	\$87,00
12NUV	ENGINE, DIESEL {MaxxForce 9} EPA 10, 315 HP @ 2000 RPM, 950 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed	48/5	53	\$1,410.00
	Includes : AIR COMPRESSOR AIR SUPPLY LINE Naturally-Aspirated (Air Brake Chassis Only) : ANTI-FREEZE Red Shell Rotella Extended Life Coolant; -40 Degrees F/ -40 Degrees C; for MaxxForce Engines : COLD STARTING EQUIPMENT Intake Manifold Electric Grid Heater with Engine ECM Control : CRUISE CONTROL Electronic; Controls Integral to Steering Wheel : ENGINE OIL DRAIN PLUG Magnetic : ENGINE SHUTDOWN Electric, Key Operated : FUEL FILTER Included with Fuel/Water Separator : FUEL WATER SEPARATOR Fuel/Water Separator and Fuel Filter in a Single Assembly; With Water-in-Fuel Sensor; Engine Mounted : GOVERNOR Electronic : OIL FILTER, ENGINE Spin-On Type : WET TYPE CYLINDER SLEEVES			
12THZ	FAN DRIVE {Horton Drivemaster Polar Extreme} Direct Drive Type, Two Speed, With Residual Torque Device for Disengaged Fan Speed Includes	46/-3	43	\$503.00
12UBB	: FAN Nylon RADIATOR Aluminum, Front to Back Cross Flow, Series System; 1663 Sqln Core and 885 Sqln Charge Air Cooler and 470 Sqln Low Temperature Radiator Down Flow Includes : DEAERATION SYSTEM with Surge Tank	6/-1	5	. \$0.00

Vehicle Specifications 2012 7400 SFA 6X4 (SF525)

Code	Description	F/R Wt (lbs)	Tot Wt	<u>List</u> (USA DOLLAR)
	: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps : RADIATOR HOSES Premium, Rubber			
12UXE	FEDERAL EMISSIONS for 2010; MaxxForce 9 & 10 Engines	0/0	0	\$6,000.00
12VAG	AIR CLEANER Single Element, with Integral Snow Valve and In- Cab Control	2/0	2	\$157.00
•	Includes : GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted	•		· ·
12VXT	THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel	0/0	0	\$0.00
12VZA	ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; With Ignition Switch Control for MaxxForce post 2007 Emissions Electronic Engines	0/0	0	\$45.00
12WTH	BLOCK HEATER, ENGINE {Phillips} 120 Volt/1250 Watt; With "Y" Cord From Socket in Standard Location, For a Dealer Installed Oil Pan Heater, With Extended Life Coated Metal/Plastic/Metal Material Oil Pan, for 16	4/0	4	\$82.00
	Includes : BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door			
	Notes : MPM material is single sheet composite with two layers of sheet metal sandwiching plastic material. MPM material has electrodeposition prime coat with powder coating for the final finish coat.			
12WZE	EMISSION COMPLIANCE Federal, Does Not Comply With California Clean Air Regulations	0/0	. 0	\$0.00
13ALZ	TRANSMISSION, AUTOMATIC (Allison 3000_RDS_P) 4th Generation Controls; Close Ratio, 5-Speed, With Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.	208/44	252	\$6,917.00
	Includes : OIL FILTER, TRANSMISSION Mounted on Transmission : TRANSMISSION OIL PAN Magnet in Oil Pan			
13WAW	OIL COOLER, AUTO TRANSMISSION (Modine) Water to Oil, for Allison or CEEMAT Transmission	25/0	25	\$667.00
13WBN	TRANSMISSION SHIFT CONTROL (Allison) T-Bar Type; for Allison 3000 & 4000 Transmission	0/0	. 0	\$371.00
13WLP	TRANSMISSION OIL Synthetic; 29 thru 42 Pints	0/0	0	\$203.00
13WUC	ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction	0/0	0	\$0.00
13WYH	TRANSMISSION TCM LOCATION Located Inside Cab	0/0	0	\$141.0 0
13WYL	SHIFT CONTROL PARAMETERS Allison Performance Programming in Primary and Allison Economy Programming in Secondary	0/0	0	\$0.00

<u>Vehicle Specifications</u> 2012 7400 SFA 6X4 (SF525)

<u>Code</u>	Description	F/R Wt (lbs)	Tot Wt (lbs)	<u>List</u> (USA DOLLAR)
14803	BUSHINGS, EQUALIZER BEAM Bronze Center Bushings; for Hendrickson Suspension	0/0	0	\$176.00
14GVJ	AXLE, REAR, TANDEM {Meritor MT-40-14X-4DER-P} Single Reduction, 0.433"(11mm) Wall Housing Thickness, 40,000-lb Capacity R Wheel Ends, Driver Controlled Locking Differential in Rear-Rear Axle, Lube Oil Pump. Gear Ratio: 5.86	0/30	30	\$1,129.00
	Includes : POWER DIVIDER LOCK Electric over Air Operated, Cab Control with Indicator Light : REAR AXLE DRAIN PLUG (2) Magnetic, For Tandem Rear Axle	÷		
	Notes : The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.	,	·	· · · · · ·
14UMB	SUSPENSION, REAR, TANDEM {Hendrickson HMX-400-52} Walking Beam Type 52" Axle Spacing; 40,000-lb Capacity, With Rubber End Bushings, Transverse Torque Rods, Less Shock Absorbers	0/125	125	\$1,032.00
·	Includes : CROSSMEMBER, SUSPENSION Stamped Steel Double Dogbone			
	Notes : The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.			
14WBV	SHOCK ABSORBERS, REAR (4) for Hendrickson HMX Suspension Only, Mounted from Frame to Beam	0/31	31	\$478.00
15LKG	FUEL/WATER SEPARATOR With Thermostatic Fuel Temperature Controlled Electric Heater, and Filter Restriction/ Change Indicator, Includes Standard Equipment Water-in-Fuel Sensor	5/0	5	\$64.00
15SET	FUEL TANK Top Draw, D Style, Non Polished Aluminum, 100 U.S. Gal., 378.5 L Capacity, 23.0" Tank Depth, Mounted Left Side Under Cab	-28/-8	-36	\$367.00
16030	CAB Conventional	0/0	0	\$0.00
	Includes : ARM REST (2) Molded Plastic; One Each Door : CLEARANCE/MARKER LIGHTS (5) Flush Mounted : COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window : CUP HOLDERS Two Cup Holders, Located in Lower Center of Instrument Panel : DOME LIGHT, CAB Rectangular, Door Activated and Push On- Off at Light Lens, Timed Theater Dimming, Integral to Console, Center Mounted : GLASS, ALL WINDOWS Tinted			

Vehicle Specifications 2012 7400 SFA 6X4 (SF525)

August 04, 2011

<u>Code</u>	Description	F/R Wt (lbs)	Tot Wt	<u>List</u> (USA DOLLAR)
	: GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side : GRAB HANDLE, CAB INTERIOR (2) Front of "B" Pillar Mounted, One Each Side : INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color : STEP (4) Two Steps Per Door	(idd)	(130)	(00.00200)
16HBA	GAUGE CLUSTER English With English Electronic Speedometer	0/0	0	\$0.00
	Includes : GAUGE CLUSTER (6) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic), Tachometer (Electronic), Voltmeter, Washer Fluid Level : ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout : WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage (Visual and Audible)			
16HGH	GAUGE, OIL TEMP, ALLISON TRAN	1/0	1	\$48.00
16HHE	GAUGE; AIR CLEANER RESTRICTION (Filter-Minder) With Black Bezel Mounted in Instrument Panel	2/0	2	\$30.00
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0	\$0.00
16JNV	SEAT, DRIVER {National 2000} Air Suspension, High Back With Integral Headrest, Cloth, Isolator, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, -3 to +14 Degree Back Angle Adjust	0/0	0	\$232.00
	<u>Includes</u> : SEAT BELT 3-Point, Lap and Shoulder Belt Type			7
16PHX	SEAT, PASSENGER {Gra-Mag} Non Suspension, High Back, Fixed Back, Integral Headrest, Cloth	0/0	0	\$43.00
	Includes : SEAT BELT 3-Point, Lap and Shoulder Belt Type			
16SDG	MIRROR, CONVEX, LOOK DOWN {Lang Mekra} Right Side; 6" x 10 1/4", With Bright Finish	2/0	2	\$57.00
16SDU	MIRRORS (2) {Lang Mekra} Styled; Rectangular, 7.09" x 15.75" & Integral Convex Both Sides, 102" Inside Spacing, Breakaway Type, Heated Heads Thermostatically Controlled, Power Both Sides, Clearance Lights LED, Bright Finish Heads & Brackets	8/0	8	\$443.00
16SEE	GRAB HANDLE Chrome; Towel Bar Type With Anti-Slip Rubber Inserts; for Cab Entry Mounted Left Side Only at "B" Pillar	3/0	3	\$118.00
16SJV	MIRROR, CONVEX, HOOD MOUNTED {Lang Mekra} Single, Heated, Bright, Right Side	5/0	5	\$177.00
16VCC	SEAT BELT All Orange; 1 to 3	0/0	0	\$26.00
16VHX	CAB MOUNTING HEIGHT EFFECTS High Cab in Lieu of Mid High Cab Mounting (Approx. 4.5")	0/0	0	\$0.00
16VSL	WINDSHIELD Heated, Single Piece	0/0	0	\$632.00
16WBY	ARM REST, RIGHT, DRIVER SEAT	3/0	3	\$39.00

Proposal: 14515-01

<u>Vehicle Specifications</u> 2012 7400 SFA 6X4 (SF525)

Code	Description	F/R Wt (lbs)	Tot Wt	<u>List</u> (USA DOLLAR)
16WCT	AIR CONDITIONER {Blend-Air} With Integral Heater & Defroster	41/6	47	\$823.00
	Includes : HEATER HOSES Premium : HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps : REFRIGERANT Hydrofluorocarbon HFC-134A			
16WJS	INSTRUMENT PANEL Center Section, Flat Panel	0/0	0	\$0.00
16WJU	WINDOW, POWER (2) And Power Door Locks, Left and Right Doors, Includes Express Down Feature	5/0	5	\$367.00
16WKY	HVAC FRESH AIR FILTER	0/0	0	\$0.00
16WRZ	CAB INTERIOR TRIM Premium	0/0	0	\$304.00
	Includes : "A" PILLAR COVER Molded Plastic : CAB INTERIOR TRIM PANELS Cloth Covered Molded Plastic, Full Height; All Exposed Interior Sheet Metal is Covered Except for the Following: with a Two-Man Passenger Seat or with a Full Bench Seat the Back Panel is Completely Void of Covering : CAB SOUND INSULATION Includes Dash and Engine Cover Insulators : CAB, INTERIOR TRIM, CLOSEOUT Lower Dash Closeout Panel; Molded Plastic; Under Instrument Panel Driver Side : CONSOLE, OVERHEAD Molded Plastic; With Dual Storage Pockets with Retainer Nets, CB Radio Pocket, Speakers, and Reading Lights : COURTESY LIGHT (2) Mounted In Front Map Pocket Left and Right Side : DOOR TRIM PANELS with Cloth Insert on Bolster Driver and Passenger Doors : FLOOR COVERING Rubber, Black : GAUGE, TEMPERATURE, AMBIENT Includes Compass Readout and Wiring and Sensor With Display Unit Mounted in Cluster : HEADLINER Soft Padded Cloth : INSTRUMENT PANEL TRIM Molded Plastic with Black Center Section : STORAGE POCKET, DOOR (2) Molded Plastic (Carpet Texture), Full-Length; Driver and Passenger Doors : SUN VISOR (3) Padded Vinyl: 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Vanity Mirror and Toll Ticket Strap, plus 1 Auxiliary Visor (Front Only), Driver Side			
16WSK	CAB REAR SUSPENSION Air Bag Type	0/0	0	\$0.00
16XWD	SUNSHADE, EXTERIOR Aerodynamic, Painted Roof Color, Includes Integral Clearance/Marker Lights	15/2	17	\$203.00
16XWJ	WINDSHIELD WIPER BLADES Snow Type	2/0	2	\$26.00
16XXC	COWL TRAY LID	8/3	11	\$200,00
26DHJ	WHEEL, SPARE, DISC 22.5" Non-Polished Aluminum, 10-Stud (285.75mm BC) Hub Piloted, Flange Nut, Metric Mount, 9.00 DC Rim, for Front Application Only	0/62	62	\$515.00

Vehicle Specifications 2012 7400 SFA 6X4 (SF525)

August 04, 2011

Code	Description		Tot Wt	List
27DMY	WHEELS, FRONT DISC; 22.5" Non-Polished Aluminum, 10- Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 9.00 DC Rims; With Steel Hubs	(lbs) -35/0	(lbs) -35	(USA DOLLAR) \$621.00
	Notes : Aluminum Wheels not Painted or Coated : Compatible Tire Sizes: 12R22.5, 295/75R22.5, 295/80R22.5, 315/80R22.5			
28DMB	WHEELS, REAR DUAL DISC; 22.5" Non-Polished Aluminum, 10-Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs	0/-280	-280	\$2,080.00
	Notes : Aluminum Wheels not Painted or Coated : Compatible Tire Sizes: 11R22.5, 12R22.5, 255/70R22.5, 255/80R22.5, 265/75R22.5, 275/70R22.5, 275/80R22.5, 295/75R22.5, 295/80R22.5			
29007	TIRE, SPARE Equal to Model Standard	45/46	91	\$536.00
	Notes : NOTE: Only One Spare Tire per Truck Ordered. Order Must Reflect Number of Tires Required (Including Spare). 10-Digit Tire Code and Spare Rim/Wheel Code Must be Specified.	• .		
60AAG	BDY INTG, REMOTE POWER MODULE Mounted Inside Cab behind Driver Seat; Up to 6 Outputs & 6 Inputs, Max. 20 amp. per Channel, Max. 80 amp Total (Includes 1 Switch Pack With Latched Switches)	0/0	0	\$531.00
7382130121	(8) TIRE, REAR 11R22.5 G182 RSD (GOODYEAR) 496 rev/mile, load range H, 16 ply	0/176	176	\$1,368.00
7772540125	(3) TIRE, FRONT 315/80R22.5 G287 MSA (GOODYEAR) 485 rev/mile, load range L, 20 ply	99/0	99	\$1,806.00
	Total of Product Features			\$122,926.00
	Cab schematic 100GM			
	Location 1: 4015, Dk Lemon Yellow (Prem)			
	Chassis schematic N/A			
	Total Component Weight:	8968/8043	17011	
	Total List Price Including Options:			\$122,926.00

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.

ENGINE, DIESEL (0012NUV) ATTACHMENTS: 0004619 (TRAILER CONNECTIONS)

<u>Parameter</u>	<u>Value</u>	UOM
Max Vehicle Speed:7902	61	MPH
Max Eng Speed w/Speed Fault:7901	2200	N/A
IDLE Shutdown Timer Mode:7400	OFF	N/A
IDLE Shutdown Time:7401	5	MIN
ISD - Max Intake Air Temp:7402	44	C
Cruise Control - MIN Veh SP:7603	35	MPH
Cruise Control - MAX Speed:7604	60	MPH
Retarder Mode	COM-LTCH	N/A
Service Interval - Enable:9500	OFF	N/A
Service Interval - Distance:9503	12000	MILES
Service Interval - Run Time:9502	450.0	HOURS
Service Interval - Fuel Used:9501	1500	GALLONS
PTO - Max Vehicle Speed:7501	5	MPH
PTO - Vehicle Speed Override:7518	AFFCTRPS	N/A
PTO - Max Engine Speed:7508	2000	RPM
PTO - Ramp Rate:7507	100	RPM/SEC
PTO - Driveline Mode:9301	NEUTRLOP	N/A
Remote Pedal - Enable:7504	NO	N/A
Remote Pedal - Return To 0 Req:7513	RTZ-NOT	N/A
Remote Pedal - IN-CAB override:7523	AFFCTRPS	N/A
Remote Pedal - Driveline OVRD:7522	AFFCTRPS	N/A
Customer Password:8700	0000	N/A

These Electronic Parameters have been successfully finalized

Financial Summary 2012 7400 SFA 6X4 (SF525)

August 04, 2011

(USA DOLLAR)

Description	,	<u>Price</u>
Factory List Prices:		
Product Items	\$122,926.00	
Service Items	\$0,00	
Total Factory List Price Including Options:		\$122,926.00
Gledhill Snow Plow Hitch	\$4,532.00	
Diagnostic & trouble shooting	\$500.00	
mechanics training - Center City	•	
Install safety Equip CCi	\$195.00	
P & D Center City	\$0.00	
Total Preparation And Delivery:		\$5,227.00
Freight Charge	\$1,775.00	
Total Freight:		\$1,775.00
Total Factory List Price Including Freight:		\$129,928.00
Less Customer Allowance:		(\$38,595.00)
Total Vehicle Price:		\$91,333.00
Total Warranty:		\$4,237.00
Total Sale Price:	•	\$95,570.00
Total Per Vehicle Sales Price:		\$95,570.00
Net Sales Price:		\$95,570.00

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:	Accepted by Purchaser
Official Title and Date	Firm or Business Name
Authorized Signature	Authorized Signature and Date
This proposal is not binding upon the seller without Seller's Authorized Signature	
	Official Title and Date

<u>Warranty</u> 2012 7400 SFA 6X4 (SF525) August 04, 2011

(USA DOLLAR)

Description

84 - Month 100,000 mile extended warranty contract 213568 \$6240. & 216268 \$2234.

Price

4237.00

Total Warranty: \$4,237.00



Quote

127 Walnut Street * Lindenwood, IL 61049 * Tel: (888) 825-7323

Price Quote Number:

Q-003394

Date: 8/8/2011

Prepared By:

Dawn Sage

Reference: CITY OF COLUMBUS- SADS

Company: Misc Customer Quote

Name: JERRY BUCKLEY

Address: CITY OF COLUMBUS OH

City: COLUMBUS

State: OH

Zip: 43219

Phone: 614-496-0031

Fax:

Approval:

Estimated Freight:

Terms:

Delivery:

F.O.B.

included

30 Days

60 Days

Lindenwood, IL

Ref#	Product and Description	Discounted Price	Qty	Extended Price
00002-463-97	SADS made to the specifications listed in OH bid number 030-11 section number 3 line item: 12 for undertailgate spreader, Contract Expiration 5/31/12.	\$ 2,364.00	2	\$ 4,728.00
		T	otal:	\$ 4,728:00

Exceptions / Comments:			 444

in Addition to Swenson Spreader, it is the dealer's responsibility to review specifications. Dealer is responsible to ensure that the truck meets all gross vehicle weight requirements. The quoted price includes only what is described above. Swenson Spreader is not responsible for options or equipment either implied or intended. Delivery date subject to change. Please check delivery when placing order. This quote is valid for thirty days from the date above. We request a bid tab to be returned for all quotes.



2550 West Fifth Avenue Columbus, OH 43204-3815 (614) 488-2861 (800) 233-7568 Fax (614) 488-0019

Date:

August 31, 2011

To:

City of Columbus

Attention:

Jerry Buckley

Re:

Liquid Brine System

Sender:

Jim Borowski

YOU SHOULD RECEIVE 1 PAGE(S), INCLUDING THIS COVER SHEET.
IF YOU DO NOT RECEIVE ALL THE PAGES, PLEASE CALL.

Per your request PENGWYN is pleased to quote the following:

CS-80

80 Gallon Cab Shield Mounted System

per ODOT contract 034-12 Effective 9/1/11 through 8/31/12

Section 1 Pre-Wetting Systems Item 5 Spec. Item 5L

\$1,650.00 each

2 Units

\$3,300.00 total

Terms and conditions per ODOT contract:

Delivery 45 days A.R.O. Terms net 30 days. F.O.B. delivery point.



2550 West Fifth Avenue Columbus, OH 43204-3815 (614) 488-2861 (800) 233-7568 Fax (614) 488-0019

Date:

July 27, 2011

To:

City of Columbus

Attention:

Jerry Buckley

Fax:

Re:

Central Hydraulic System Tandem Axle

Sender:

Jim Borowski

YOU SHOULD RECEIVE 1 PAGE INCLUDING THIS COVER SHEET.
IF YOU DO NOT RECEIVE ALL THE PAGES, PLEASE CALL.

Per your request PENGWYN is pleased to quote the following:

485-EBPC-IT-TAS-LH

Tandem Axle Truck

Item 1a Central Hydraulic control System	\$9,274.
Item 1a Central Hydraulic control System 485-EBP-IT-SAS-LH	\$9,274

Item 6a Hydraulic Plow Counter-Balance \$ 735.00

Item 7a High Capacity Hydraulic Pump <u>\$ 945.00</u>

TOTAL \$10,954.00

00

NOTE: Above price per ODOT contract 035-11. Contract expires 7/31/12

Delivery 30-45 Days A.R.O. Net 30 Days F.O.B. Columbus, Ohio

Jim Borowski jim.borowski@pengwyn.com 614-488-2861 614-557-3219 (cell)



2550 West Fifth Avenue Columbus, OH 43204-3815 (614) 488-2861 (800) 233-7568 Fax (614) 488-0019

Date:

July 27, 2011

To:

City of Columbus

Attention:

Jerry Buckley

Fax:

r ax. Re:

Central Hydraulic System Single Axle

Sender:

Jim Borowski

YOU SHOULD RECEIVE 1 PAGE INCLUDING THIS COVER SHEET.
IF YOU DO NOT RECEIVE ALL THE PAGES, PLEASE CALL.

Per your request PENGWYN is pleased to quote the following:

485-EBPC-IT-SAS-LH

Single Axle Truck

Item 1a Central Hydraulic control System 485-EBP-IT-SAS-LH

\$9,274.00

405 EB1 11 5710 EM

\$ 735.00

Item 6a Hydraulic Plow Counter-Balance

 \mathbf{C}

\$10,009.00

NOTE: Above price per ODOT contract 035-11. Contract expires 7/31/12

TOTAL

Delivery 30-45 Days A.R.O. Net 30 Days F.O.B. Columbus, Ohio

Jim Borowski jim.borowski@pengwyn.com 614-488-2861 614-557-3219 (cell)



Public Safety Equipment 8495 Estates Ct Plain City, Ohio 43064 866-320-7277 Fax: 614-873-7205 www.parrpse.com

Quote

Date	Quote #
8/16/2011	4024

Columbus Transportation Division	
Attn: Jerry Buckley	
09 N. Front St., 4th Floor	
Columbus, Ohio 43215-9023	
,	

		Project	Terms	Rep		FOB	Entered By
			Net 30		I	Plain City,Oh	Τ₽
Item		Descript	ion	Qt	y	Cost	Total
ODOT05L	ODOT #ODO	2012 Plow Truck warning 6 head LED truck lightin T05L	lights system g system complete		2	1,215.00	2,430.12
	Each s	ystem contains: IAF, 2 AR36EA40LED, 2	2 TIR3A, 2 RFLANGE	A .			
	ODOT	Contract 187-12 - Dump	Truck LED system				
		:					
					Tot	al	\$2,430.12

PLEASE REFER TO THIS NUMBER ALWAYS

THE GLEDHILL ROAD MACHINERY CO.

Manufacturers of Road Maintenance Machinery

AREA 419, 468-4400 FAX 419/488-4004 Gallon. Ohio

44833, P. O. BOX 567

DATE: August 3, 2011

TO: City of Columbus 4211 Groves Road Columbus, OH 43232

ATTENTION:

JERRY BUCKLEY - Fleet Management Division GENTLEMEN:

IN RESPONSE TO YOUR verbal INQUIRY DATED August 3, 2011 INQUIRY FOR snowplow pricing WE ARE PLEASED TO QUOTE YOU THE FOLLOWING FIRM PRICES WHICH WILL REMAIN IN EFFECT FOR SIXTY DAYS FROM THIS DATE. STATE OF OHIO - DAS - STS QUOTATION INDEX NO. STS515, CONTRACT NO. 800008

QTY.	DESCRIPTION	VIT PRICE	AMOUNT	
l ea.	Gledhill Road Machinery Company Snowplow Model 10HSBPRT-T	E-QCP-LL.		
	10HSBPRT Snowplow		\$ 9,222.08	List
	P-111-76 Cushion Valve		234.08	List
	SPO-4 Trip Cutting Edge w/curb shoes, 4 springs			List
	QCP-P Plow Portion		266.56	List
	7784-A2-E 5/8" x 6" x 10' 1g. snowplow blade		40.26	List
	Rubber Belting Bolt-On Baffle, 1/2" x 12" x 10' lg			List
	SPO-62 Install Rubber Baffle		108.64	List
	LEVEL-LIFT5 Level-Lift for PRT all & Spanner Bar 14218-DE		777.28	List
	16697-C-E Moldboard Shoe, Cast, 6", Pr		271.04	List
			\$12,271.78	List
	LESS 23% STS DISCOUNT	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	2,822.51	 -

\$ 9,449.27 Net

to City of Columbus

Snowplow will be 10' long, 42" high, # 10 ga. steel moldboard, one piece trip cutting edge, hydraulic reversible with two (2) 4" x 12" double acting reversing cylinders, tube table, tube A-frame, QCP plow portion, Level-Lift system, cushion valve, mushroom shoes, moldboard shoes, 5/8" x 6" cutting edge, rubber baffle installed.

ABOVE PRICES ARE AS SHOWN

F.O.B. DESTINATION

INSTALLATION CHARGES: n/a
TRANSPORTATION CHARGES: Included
SHIPPING PROMISE: 70 Days after receipt of order
DISCOUNT: Shown above, 23%
TERMS: 2% - 15 Days, Net 30

If you have any questions, please call me. Phone: 419-468-4400, Cell: 419-565-4077

THANKS !

THE GLEDHILL ROAD MACHINERY CO.

Rick Moore - National Sales Manager

PLEASE REFER TO THIS NUMBER ALWAYS

THE GLEDHILL ROAD PLACHINERY GO.

Manufacturers of Road & Maintenance Machinery

AREA 419, 468-4400

Galion, Ohio

44833, P.O.BOX 567

DATE: August 3, 2011

TO: City of Columbus 4211 Groves Road Columbus, OH 43232

ATTENTION:

JERRY BUCKLEY - Fleet Management Division

GENTLEMEN:

IN RESPONSE TO YOUR verbal INQUIRY DATED August 3, 2011 INQUIRY FOR snowplow pricing WE ARE PLEASED TO QUOTE YOU THE FOLLOWING FIRM PRICES WHICH WILL REMAIN IN EFFECT FOR SIXTY DAYS FROM THIS DATE. STATE OF OHIO - DAS - STS QUOTATION INDEX NO. STS515, CONTRACT NO. 800008

QTY. l ea.	DESCRIPTION UNIT PRICE Gledhill Roa'd Machinery Company Snowplow Model 11HSBPRT-TE-QCP-LL.	AMOUNT
	11HSBPRT Snowplow	\$ 9,337.44 List
	P-111-76 Cushion Valve	234.08 List
	SPO-4 Trip Cutting Edge w/curb shoes, 4 springs	1,171.52 List
	QCP-P Plow Portion	266.56 List
	7784-A3-E 5/8" x 6" x 11' 1g. snowplow blade	44.30 List
	Rubber Belting Bolt-On Baffle, 1/2" x 12" x 11' 1g	
	SPO-62 Install Rubber Baffle	108.64 List
	LEVEL-LIFT5 Level-Lift for PRT all & Spanner Bar 14218-DE	
	16697-C-E Moldboard Shoe, Cast, 6", Pr	
		\$12,405.74 List
	LESS 23% STS DISCOUNT	2,853.32

\$ 9,552.42 Net to City of Columbus

Snowplow will be 11' long, 42" high, # 10 ga. steel moldboard, one piece trip cutting edge, hydraulic reversible with two (2) 4" x 12" double acting reversing cylinders, tube table, tube A-frame, QCP plow portion, Level-Lift system, cushion valve, mushroom shoes, moldboard shoes, 5/8" x 6" cutting edge, rubber baffle installed.

ABOVE PRICES ARE AS SHOWN

F.O.B. DESTINATION

INSTALLATION CHARGES: N/A
TRANSPORTATION CHARGES: Included
SHIPPING PROMISE: 70 Days after receipt of order
DISCOUNT: Shown above, 23%
TERMS: 2% - 15 Days, Net 30
COMMENTS

If you have any questions, please call me. Phone: 419-468-4400, Cell: 419-565-4077

THANKS !

THE GLEDHILL ROAD MACHINERY CO.

sy Mille Morre

Rick Moore - National Sales Manager



2550 West Fifth Avenue Columbus, OH 43204-3815 (614) 488-2861 (800) 233-7568 Fax (614) 488-0019

Date:

July 27, 2011

To:

City of Columbus

Division of Planning & Operations

1881 E 25th Avenue Columbus OH 43215

Attention:

Jerry Buckley

Fax:

Re:

Single Axle Assembly Quote

Sender:

Jim Borowski

YOU SHOULD RECEIVE 1 PAGE INCLUDING THIS COVER SHEET.
IF YOU DO NOT RECEIVE ALL THE PAGES, PLEASE CALL.

Per your visit PENGWYN is pleased to quote the following:

Labor and Hardware to install City of Columbus material on International cab and chassis.

Labor and parts

\$16,500.00

To be Invoiced and paid as each truck is completed.

Installation of communication equipment supplied by City of Columbus

\$1,000.00

To be invoiced and paid as each communication equipment installation is completed.

NOTE: CITY OF COLUMBUS TO DELIVER COMMUNICATION EQUIPMENT 7-14 DAYS AFTER DELIVERY OF CAB AND CHASSIS TO PENGWYN !!!!

NOTE: SEE COVER LETTER FOR ADDIONAL INFORMATION

NOTE: ABOVE PRICING IS PER EACH TRUCK !!!!

Quote good for 90 Days F.O.B. Columbus, Ohio

Jim Borowski jim.borowski@pengwyn.com 614-488-2861 614-557-3219 (ceil)



2550 West Fifth Avenue Columbus, OH 43204-3815 (614) 488-2861 (800) 233-7568 Fax (614) 488-0019

Date:

July 27, 2011

To:

City of Columbus

Division of Planning & Operations

1881 E 25th Avenue Columbus OH 43215

Attention:

Jerry Buckley

Fax:

Re;

Tandem Axle Assembly Quote

Sender:

Jim Borowski

YOU SHOULD RECEIVE 1 PAGE INCLUDING THIS COVER SHEET, IF YOU DO NOT RECEIVE ALL THE PAGES, PLEASE CALL.

Per your visit PENGWYN is pleased to quote the following:

Labor and Hardware to install City of Columbus material on International cab and chassis.

Labor and parts

\$17,000.00

To be Invoiced and paid as each truck is completed.

Installation of communication equipment supplied by City of Columbus

\$1,000.00

To be invoiced and paid as each communication equipment installation is completed.

NOTE: CITY OF COLUMBUS TO DELIVER COMMUNICATION EQUIPMENT 7-14 DAYS AFTER DELIVERY OF CAB AND CHASSIS TO PENGWYN !!!!

NOTE: SEE COVER LETTER FOR ADDIONAL INFORMATION

NOTE: ABOVE PRICING IS PER EACH TRUCK!!!!

Quote good for 90 Days F.O.B. Columbus, Ohio

Jim Borowski jim.borowski@pengwyn.com 614-488-2861 614-557-3219 (cell)



2550 West Fifth Avenue Columbus, OH 43204-3815 (614) 488-2861 (800) 233-7568 Fax (614) 488-0019

Date:

August 8, 2011

To:

City of Columbus

Attention:

Jerry Buckley

Fax:

Re:

Bed Replacement on Single Axle

Sender:

Jim Borowski

YOU SHOULD RECEIVE 2 PAGE INCLUDING THIS COVER SHEET. IF YOU DO NOT RECEIVE ALL THE PAGES, PLEASE CALL.

Per you request, follows is a general estimate to install new stainless steel bed provided by the City on City of Columbus single axle dump truck that are delivered without bed or sub frame.

Work to include the following

Clean up frame and drill new holes as needed

Set and weld sub frame

Install bulkhead brackets

Hose to bulkheads

Mount bed

Attach cab shield

Install oak boards and brackets

Install level switch arrangement

Install warning lights on bed

Install strobes on rear bed post

Install brake lights

Hose from bulkhead to posts

Install old spreader and mounting plates removed by city

Install ladder and shovel holder

Estimated Parts and Labor to perform above

\$7,400.00 per truck

5 Bed installs

\$37,000.00 total

Above is a general estimate. Exact price to be provided upon examination of each individual truck on which work is to be preformed.

Above does not include Tarp or Vibrator or installation of these items.

Delivery 30-45 Days A.R.O. Net 30 Days F.O.B. Columbus, Ohio

Jim Borowski jim.borowski@pengwyn.com 614-488-2861 614-557-3219 (cell)

Thank You for the Quote Opportunity and We Look Forward To the Order

	•	
		ļ
		-
		American III
		2
		Pall and
		1
•		

		Î
		}
		<u> </u>
		1
		amount of the second of the se
		1
		1
		!
		Phrasa I III
		Personal Investment
		And and the second seco
		Parami en de la companya de la compa
		Baral politica consistence de la Région de l
		hardine dinyemba de Malaina
		hand on the process of the decision process.
		Barat job funcional de Bilinappio octobre de la Regional de Bilinappio octobre de la Regional de
		Baral pro-finance de di Educaryano vano e vere
		The analysis of the disconnection of the disconnect
		Barat i no tennementale del distanza del constanza del con
		Валация в подпасня в в выбализация в подпасня в подпасн
		Baralli prod. Barayanan de di Malian projetto Parado Consessivo de descripcio necessivo de
		litar i i poli timo interiori di di di Administrati di Santa di Sa
		The state of the s
		hand for the second of the sec
		Basal i poli financiani gali di Zimmogli Domar de escolo di poli dependenti indici di generale de del
		Baral (100 tennamen) de le Malamente de la Mal
		The self of the self-the self-
		litar i i pri li maniming qi di dizimingili berindi diseri devisi depende di pri maniming di diseri di pri di di
		ltarat ja võitamannat des sõi kõõimannatava vasta Väändi Avanda väändä väändä sõi käändä jäändä jäändä jäändä
		Rasall politicisco mais e debisionis proprio mais e considerazione del proprio
		lter i i i i i i i i i i i i i i i i i i i
		ltara i poli tempembili de l'édicionne processo de reconstruir de de consideration de consideration de des de d
		lteral politica en de el de la deservación de conservación per la conservación de la defenda de la defenda de l
		lter i i i i i i i i i i i i i i i i i i i
		lter al politicis mentide de l'Administrative de control de politicis de considerative de l'administrative de d
		the all to be transmitted to the decomposition of t
		lter Hinnessenge bl. d. mengebrong dengengengeng delak deremberaden proposition delak delak penderang delak de
		line i poli immensi de il delimente i poste de construcción de la descripción de la delimente de construcción de la delimente deli
		ltered printered de Bibliographic versit versit Nordonneum printig de annobel authorization de Parlichande en de Bibliographic de l'est de
		lter Hirokinia maga bid di mangabang di propinsi ngabigi di propinsi di propin
		land to be the second of the s
		tara i poli insuente de Principa en este de especia de especia de despecia de despecia de despecia de despecia
		lter Her benemen ge bl. d. ammye brond e foreste de general and de general and de general and de general de ge
		hard to be the second of the s
		tara i poli intermenta de Principo en estro de Consecuente estra de Consecuente de Principo de Consecuente de C
		hard in the intermedial and the second secon
		had bed in the design of the design of the second s
		tara i poli imperimenta e de de de de constitución de constitución de constitución de
		had in the intermediate of the state of the
		tara Hari banangga bid dangga bangga pengganya dangga bangga penggangga penggangga pengganggangganggangganggang
		In all the binness and the control of the control of the binness of the binness of the control o
		In all the immediate dependency of the dependency of the planets of the dependency of the planets of the dependency of the planets of the other of the dependency of the planets of the other other of the other of the other other of the other other of the other o