

November 18, 2021
Our 92nd Year

Ship To:
CITY OF COLUMBUS
3500 INDIANOLA AVE
Columbus, OH 43214
US

Bill To:
CITY OF COLUMBUS
4211 GROVES RD
Columbus, OH 43232-4104
US

Attn: JOHN KING
Phone:
Email:

Account Manager: John Travis Founds
Technical Sales Rep: Joe Kedanis

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	<u>Unit</u>	
1.	Altec Model TA60 Articulating Telescopic Aerial Device with a fiberglass upper boom and fiberglass insulator in the articulating arm and a proportional joystick upper control and toggle switches. Built in accordance to ALTEC's standard specifications and to include the following features:	1
2.	Automatic Upper Boom Stow Securing System with support cradle.	1
3.	Pedestal, Rear Mount, High Cab Height - includes 43 inch (1092 mm) pedestal height, 91.5 inch (2324 mm) mast height - recommended for T55 and TA60, installed in tall cab height chassis	1
4.	219 Single Two-Man Platform - Platform end mounted, rotates 180 degrees around boom tip. Platform has a capacity of 600lbs without liner. This option does not include material handling.	1
5.	999 - Custom Outrigger Controls	1
<u>Sales Text: Manual</u>		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
6.	259 Polyethylene platform liner for two man platform, 50 kV rating (minimum)	1
7.	Engine Start/Stop & Secondary Stowage System: 12 VDC powered motor and pump assembly for temporary operation of the unit in a situation wherein the primary hydraulic	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	source fails. Electric motor is powered by the chassis battery. This feature allows the operator to completely stow the booms, platform, and outriggers. Secondary Stowage & Start/Stop is activated with an air plunger at the platform or momentary switch at the lower control station and outriggers.	
	<u>Sales Text:</u> Include two speed throttle Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
8.	241 - Outrigger A-Frame with Flat-shoe - provides 149 inch (3785 mm) maximum spread outside to outside of shoe.	1
9.	240 Modified flat-shoe, A-frame, Fixed Shoe, Outrigger installed at rear of body, with 101 inches (2565 mm) of spread at maximum penetration.	1
10.	Custom unit color (specify color code).	1
	<u>Sales Text:</u> NAV4015 Last Updated By: Joe Kedanis on 15-DEC-2020 16:15	
11.	Custom Above Rotation Color	1
	<u>Sales Text:</u> NAV4015 Last Updated By: Joe Kedanis on 15-DEC-2020 16:15	
12.	Custom Pedestal/Tower Color	1
	<u>Sales Text:</u> NAV4015 Last Updated By: Joe Kedanis on 15-DEC-2020 16:15	
13.	Custom Inner Outrigger Leg Color	1
	<u>Sales Text:</u> NAV4015 Last Updated By: Joe Kedanis on 15-DEC-2020 16:15	
14.	Custom Outrigger Housing Color	1
	<u>Sales Text:</u> NAV4015 Last Updated By: Joe Kedanis on 15-DEC-2020 16:15	
15.	Custom Hydraulic Oil not Required, Compatible with Standard	1
16.	HYBRID READY UNIT: For personnel, single platform machines. Unit will be manufactured with all the necessary components including modules and controls to interface to a hybrid system.	1
	<u>Unit and Hydraulic Acc.</u>	
17.	Platform Cover, 24 X 48, Soft Vinyl	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
18.	Scuff Pad, 24" x 48", With Step (For use with Platform Liner)	1
19.	Standard Spacer between Subbase and frame for hose routing and ease of maintenance.	1
20.	Reservoir, 30 Gallon, Triangular, Mounted in Cargo Area	1
21.	TA Series Subbase	1
22.	Temperature Sight Gauge	1
23.	HVI-22 Hydraulic Oil (Standard).	38
24.	JEMS Pump, Right Hand Rotation	1
25.	Hot shift PTO for automatic transmission	1
26.	Muncie PTO (Altec Standard)	1
27.	Standard Altec PTO/Machine Functionality: PTO won't engage until parking brake is set.-Once parking (holding) brake is set, PTO and machine functions are enabled.-If parking (holding) brake is disengaged, both PTO and machine functions are disabled.	1
28.	Altec recommends any connection made to the tool circuit be done with Non-Conductive hose. If ordering a Hose reel, Altec recommends ordering a hose reel with Non-Conductive hose. The lower tool circuit hoses may be, or become, conductive. Death or serious injury could occur if the unit becomes energized while lower tool circuit is in use.	1
29.	Spring Loaded Hose Reel, 50 FT Hose Capacity	1
<p><u>Sales Text:</u> Install on CS rear of tailshelf payout to rear. Last Updated By: Joe Kedanis on 15-DEC-2020 16:15</p>		
30.	Install Tool Circuit with Quick Disconnects, Below Rotation (Male Pressure, Female Return)	1
31.	50' Non-Conductive Hose Kit, Orange, Includes Quick Disconnects and Dust Caps (Male Pressure, Female Return)	1
32.	Custom Hydraulic Tool	1
<p><u>Sales Text:</u> H8508 Greenlee impact wrench with 10ft hose kit and QD's Last Updated By: Joe Kedanis on 23-JUL-2020 11:29</p>		
33.	Flow Divider, Optional for Variable Tool Control - for Final Assembly Installation of Tools at Tailshelf	1
34.	Additional Unit/Hydraulic Accessory	1

Sales Text: Greenlee crimping press PN 900049345

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
35.	Additional Unit/Hydraulic Accessory	1
	<u>Sales Text:</u> Greenlee impact wrench PN 701069023	
	Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
36.	Additional Unit/Hydraulic Accessory	1
	<u>Sales Text:</u> LPK1240 Greenlee crimping press with 10ft hose kit and QD's	
	Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
37.	Additional Unit/Hydraulic Accessory	1
	<u>Sales Text:</u> Hydraulic reservoir guard with lid.	
	Last Updated By: Joe Kedanis on 15-DEC-2020 16:15	
	<u>Body</u>	
38.	Altec Body	1
39.	Aluminum Body	1
40.	Body Is To Be Built In Accordance With The Following Altec Standard Specifications:	1
41.	Smooth Aluminum Floor	1
42.	Aerial Service Line With Step (ASLS)	1
43.	Finish Paint Body Custom Color (Provide Color And Code)	1
	<u>Sales Text:</u> NAV4015 to match chassis	
	Last Updated By: Joe Kedanis on 12-APR-2021 11:14	
44.	Undercoat Body	1
45.	Approximate Body Length (Engineering to Determine Final Length)	1
	<u>Sales Text:</u> 150"	
	Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
46.	94" Body Width	1
47.	46" Body Compartment Height	1
48.	18" Body Compartment Depth	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
49.	Custom Body Cargo Retaining Option	1
<u>Sales Text:</u> Non required, tailshelf has retention		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
50.	Rope Lights (LED) Around Top And Sides Of Compartment Door Facings	9
<u>Sales Text:</u> To turn on only when truck is in park.		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
51.	Stainless Steel Rotary Paddle Latches With Keyed Locks	9
52.	All Locks Keyed Alike Including Accessories (Preferred Option)	1
53.	Standard Master Body Locking System (Standard Placement Is At Rear. Sidepacks With A Throughshelf/Hotstick Door At Rear, Standard Placement Is At The Front)	9
54.	Gas Prop Rigid Door Holders On All Vertical Doors	1
55.	One Chock Holder On Each Side of Body With Retaining Lip In Fender Panel	1
56.	Hotstick Shelf Extending Full Length Of Body On Streetside	1
57.	Two Hotstick Brackets On Streetside	1
58.	Standard Drop-Down Hotstick Door For One (1) Shelf On Streetside, Stainless Steel Slam Paddle Latch With Keyed Lock	1
59.	1st Vertical (SS) - Adjustable Shelf With Removable Dividers On 4" Centers	2
60.	Custom 1st Vertical (SS) Compartmentation	1
<u>Sales Text:</u> 24"W		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
61.	2nd Vertical (SS) - Adjustable Shelf With Removable Dividers On 4" Centers	2
62.	Custom 2nd Vertical (SS) Compartmentation	1
<u>Sales Text:</u> 24"W		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
63.	3rd Vertical (SS) - Adjustable Shelf With Removable Dividers On 4" Centers	2
64.	Custom 3rd Vertical (SS) Compartmentation	1
<u>Sales Text:</u> 20"W		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		

<u>Item</u>	<u>Description</u>	<u>Qty</u>
65.	1st Horizontal (SS) - Fixed Shelf With Removable Dividers On 4 Inch Centers On Bottom of Compartment	1
66.	Custom 1st Horizontal (SS) Compartmentation	1
<u>Sales Text: 58"W</u>		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
67.	Rear Vertical (SS) - Adjustable Shelf With Removable Dividers On 4" Centers	2
68.	Custom Rear Vertical (SS) Compartmentation	1
<u>Sales Text: 24"W</u>		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
69.	1st Vertical (CS) - Partial Transverse Compartment Extending To The Rear Wall Of the Streetside	1
70.	1st Vertical (CS) - Transverse Shelf	1
71.	1st Vertical (CS) - 4 Inch High Transverse Drawer Kit On Slides, As Wide As Possible And Full Length, No Dividers (Slides To CS Only)	2
<u>Sales Text: Dividers on 6" centers. Wood lined. rated for up to 500lbs and with heavy duty latches.</u>		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
72.	Custom 1st Vertical (CS) Compartmentation	1
<u>Sales Text: 24"W,</u>		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
73.	2nd Vertical (CS) - Gripstrut Access Steps With Two (2) Sloped Grab Handles	1
74.	3rd Vertical (CS) - Adjustable Shelf With Removable Dividers On 4" Centers	2
75.	Custom 3rd Vertical (CS) Compartmentation	1
<u>Sales Text: 20"W</u>		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
76.	1st Horizontal (CS) - 4" High Drawer Kit On Slides, As Wide As Possible, Latched	4
<u>Sales Text: Dividers on 4 inch centers</u>		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
77.	Custom 1st Horizontal (CS) Compartmentation	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	<u>Sales Text:</u> 58"W Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
78.	Custom Rear Vertical (CS) Compartmentation	1
	<u>Sales Text:</u> 24"W Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
79.	36" L Aluminum Tailshelf, Width To Match Body	1
80.	Custom Aluminum Tailshelf Option	1
	<u>Sales Text:</u> 8" high removable composite retainer around all 3 sides of of tailshelf. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
81.	Smooth Aluminum Tailshelf Floor	1
82.	Inverter Storage In Remote Aluminum Enclosure, Located Outside Of Body Compartments With Provisions For Remote GFCI Receptacle In Curbside 1st Vertical	1
	<u>Sales Text:</u> Install above CS 1st and 2nd vertical. Last Updated By: Joe Kedanis on 14-JAN-2021 15:31	
83.	Aluminum Designator	1
	<u>Body and Chassis Accessories</u>	
84.	Rear Window Guard, 62" L x 20" H	1
85.	ICC (Underride Protection) bumper with integral fixed Grip Strut steps on curbside and streetside	1
86.	Swivel Style Pintle Hitch (30 000 LB MGTW with 6 000 LB MVL), 11-Bolt T-Mount, Altec Preferred (T-125 Style)	1
	<u>Sales Text:</u> 24"H load bearing surface. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
87.	Set Of D-Rings for Trailer Safety Chain, installed one each side of towing device mount.	1
88.	Send Out for Spring Build Up	1
89.	Rubber Belted Step, 12" H, 7" D, 24" W, Aluminum, Mounted Beneath Side Access Steps (Installed To Extend Approx. 2" Outward)	1
90.	Platform Access Step From Body Floor	1
91.	Platform Rest, Rigid with Rubber Tube	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
92.	Lower Boom Rest Weldment	1
93.	Mounting Brackets for Lights, Located on Lower Boom Rest	1
94.	Plastic Outrigger Pad, 18 x 18 x 1 Inch, Black With Handle	4
95.	Outrigger Pad Holder, 20" L x 20" W x 3" H, Fits 19.5" x 19.5" x 2" And Smaller Pads, Bolt-On, Bottom Washout Holes, 3/4" Lip Retainer	4
<p><u>Sales Text:</u> One near each outrigger. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29</p>		
96.	Mud Flap Without Altec Logo (Pair)	2
<p><u>Sales Text:</u> Rearward of both front and rear tires. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29</p>		
97.	Wheel Chocks, Rubber, 9.75" L x 7.75" W x 5.00" H, with 4" L Metal Hairpin Style Handle (Pair)	2
98.	Slope Indicator Assembly (Pair) For Machine With Outriggers	1
99.	Safety Harness And 4.5' Lanyard (Fits Medium To Xlarge) Includes Pouch and Placards	2
100.	Triangular Reflector Kit (Contains 3 Reflectors), Shipped Per DEPS-0042	1
101.	5 LB Fire Extinguisher With Heavy Duty Bracket, Installed	1
<p><u>Sales Text:</u> Install on CS front of body Last Updated By: Joe Kedanis on 15-DEC-2020 16:15</p>		
102.	Sight Rods, Nylon, 48 Inches, Fluorescent Orange (Pair), Mounted on Front Bumper	1
103.	Vinyl manual pouch for storage of all operator and parts manuals	1
104.	Outrigger Control Guards- Underhung Tailshelf Mount	1
105.	Additional Body/Chassis Accessory	1
<p><u>Sales Text:</u> tiered light bracket one each side of boomrest for mounting strobes, go lights, and perimeter lights. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29</p>		
106.	Additional Body/Chassis Accessory	1

Sales Text: Grab handle to extend from rear of body to rear of tailshelf on CS
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29

<u>Item</u>	<u>Description</u>	<u>Qty</u>
<u>Electrical Accessories</u>		
107.	Compartment Lights Wired To Dash Mounted Master Switch	1
108.	Lights and reflectors in accordance with FMVSS #108 lighting package. (Complete LED, including LED reverse lights)	1
109.	Altec Standard Amber LED Strobe Light with Brush Guard	2
<p><u>Sales Text:</u> One each side of boomrest Last Updated By: Joe Kedanis on 23-JUL-2020 11:29</p>		
110.	6-Position Strobes, Amber, LED, Two (2) Surface Mounted Lights In Grille, Two (2) Oval Lights On Body Sides, Two (2) Round Lights At Rear	1
<p><u>Sales Text:</u> 2 additional lights on rear CS and SS corners of body.</p> <p>8 total strobes all wired to light bar switch. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29</p>		
111.	Strobe Lights Wired Ignition Hot	1
112.	Custom Light Bar	1
<p><u>Sales Text:</u> Ecco part number ECC1200001E amber light bar with alley lights, take down lights, and controller. Install on top of cab. Last Updated By: Joe Kedanis on 03-FEB-2021 13:29</p>		
113.	Flood Light, LED, With Aluminum Housing, 4.25" W x 4.25" H, No Switch on the Light	2
<p><u>Sales Text:</u> 2 reverse lights mounted in ICC area, one each on outboard face of frame rails. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29</p>		
114.	Cargo Light LED 4 IN DIA Grommet Mounted (Tecniq #T41-WC0T-1)	1
<p><u>Sales Text:</u> Mounted in CS rear cargo wall as high up on the wall as possible. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29</p>		
115.	Perimeter/Underbody Lights, Black (Pair)	2
<p><u>Sales Text:</u> One near each outrigger. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29</p>		
116.	Remote Spot Light, LED, Permanent Mount with Wireless Dash Mounted Controls and Programmable Wireless Remote	2
<p><u>Sales Text:</u> Mount on tiered bracket one each side of boomrest. Wired battery hot. Reference DJ 682012021 for tiered bracket</p>		

<u>Item</u>	<u>Description</u>	<u>Qty</u>
Last Updated By: Joe Kedanis on 15-DEC-2020 16:15		
117.	Auxiliary Lighting Wired Ignition Hot	1
118.	Dual Tone Back-Up With Outrigger Motion Alarm	1
119.	Altec Standard Multi-Point Grounding System	3
120.	Altec Backup Camera System, 7" Color LCD Monitor, Heated Infrared Camera with Day/Night Sensor and Audio	1
121.	Install backup camera monitor on the front windshield in lieu of the rearview mirror.	1
122.	7-Way Trailer Receptacle (Pin Type) Installed At Rear	1
123.	Relocate Trailer Receptacle Supplied With Chassis	1
124.	Electric Trailer Brake Controller (Tekonsha Voyager #9030)	1
125.	Altec Modular Panel System (AMPS) - Includes Mounting Panel and Accessory Switches	1
126.	Inverter Wired Ignition Hot To Switch Mounted In Chassis Cab	1
127.	Pre-Wire Power Distribution Module (Includes Operators Manual)	1
128.	Install secondary stowage system.	1
129.	Install Remote Start/Stop system in Final Assembly.	1
130.	Install Outrigger Interlock System	1
131.	Boom Out Of Stow Indicator For Lower Boom	1
132.	Additional Electrical Accessory	1

Sales Text: Customer supplied Motorola 2 way radio installed in the cab with all needed antennas and wiring. weatherproof outside radio speaker installed and wired into the motorola radio with a selector switch for radio output selection (in cab v. outside of cab)

Last Updated By: Joe Kedanis on 23-JUL-2020 11:29

Finishing Details

133.	Finish Paint Body Accessories Custom Color (Specify Color Code)	1
------	---	---

Sales Text: NAV4015

Last Updated By: Joe Kedanis on 15-DEC-2020 16:15

<u>Item</u>	<u>Description</u>	<u>Qty</u>
134.	Altec Standard; Components mounted below frame rail shall be coated black by Altec. i.e. step bumpers, steps, frame extension, pintle hook mount, dock bumper mounts, D-rings, receiver tubes, accessory mounts, light brackets, under-ride protection, etc. Components mounted to under side of body shall be coated black by Altec. i.e. Wheel chock holders, mud flap brackets, pad carriers, boxes, lighting brackets, steps, and ladders.	1
135.	Apply Non-Skid Coating to all walking surfaces	1
136.	Heavy Duty Cargo Coating, Gator Hyde, Cargo Area Floor and Tailshelf	1
<p><u>Sales Text: Cargo area and tailshelf floor</u> Last Updated By: Joe Kedanis on 23-JUL-2020 11:29</p>		
137.	English Safety And Instructional Decals	1
138.	Vehicle Height Placard - Installed In Cab	1
139.	Placard, HVI-22 Hydraulic Oil	1
140.	Dielectric test unit according to ANSI requirements.	1
141.	Stability test unit according to ANSI requirements.	1
142.	Completed Test Forms To Be Included In The Manual Pouch	1
	A. Stability Test Form	
	B. Dielectric Test Form (For Insulating Units)	
143.	DOT Certification Required	1
<p><u>Sales Text: City of Columbus, OH</u> Last Updated By: Joe Kedanis on 15-DEC-2020 16:15</p>		
144.	Pre-delivery / Customer Validation Inspection Required	1
145.	Focus Factory Build	1
146.	Delivery Of Completed Unit	1
147.	Inbound Freight	1
148.	As Built Electrical And Hydraulic Schematics To Be Included In The Manual Pouch	1
149.	TA60 FA Installation	1
150.	JEMS 4A Hybrid System Installation	1

Hybrid

<u>Item</u>	<u>Description</u>	<u>Qty</u>
151.	JEMS 4A (Jobsite Energy Management System) for Aerial Applications	1
	<ul style="list-style-type: none"> A. Lithium Ion energy storage provides power the Jobsite Energy Management System B. The JEMS Idle Mitigation System automatically eliminates unnecessary engine idle time, manages cabin temperature heating & cooling, and maintains battery state of charge when the vehicle is in park or neutral. C. Integrated Cabin Comfort HVAC provides heating and cooling through the factory vents. D. The JEMS system automatically starts the engine and engages the transmission-mounted PTO/pump when auxiliary hydraulic power is selected from the in-cab control. E. Integral safety interlocks ensure the JEMS system operates only when the transmission is in Park/Neutral, the Parking brake is set, and the engine compartment hood is closed. 	
152.	Cargo Area Installation at Streetside Front of Body. AC 100 battery pack is installed Streetside front in cargo area of body. Must provide 9 inches of clearance off connection side of box at front of body.	1
	<p><u>Sales Text:</u> Install on top of transverse area ILO cargo floor.</p> <p>Last Updated By: Joe Kedanis on 15-DEC-2020 16:15</p>	
153.	Cabin Air, Engine Off. Provides cooled air through factory ventilation system. Temperature set points and operating status are provided on the in cab display.	1
	<ul style="list-style-type: none"> A. Cooling is provided by a supplementary air conditioning compressor. 	
154.	Cabin Heat, Engine Off. Provides heated air through factory ventilation system. Temperature set points and operating status are provided on the in cab display.	1
	<ul style="list-style-type: none"> A. Heating is provided by an electrically driven heat pump tied into the factory system. 	
155.	Inverter, 3000 Watt, Pure Sine Wave, 120 VAC (Sensata #12/3000N)	1
156.	Auxiliary Lithium Ion Power Module required for Inverter Outputs Greater Than 1200 Watts. The PM100 must be mounted near the inverter and must not be exposed to water contact or impacts from cargo.	1
157.	Extension Cord For Plug-In Charging, 50ft	1
158.	Mechanical bypass with turnkey operation used to bypass the JEMS system in the unlikely event of a system fault. Operated by a key located on top of the bypass enclosure. Installed in cab.	1
159.	PTO/ePTO Engaged Through Chassis Upfitter Switch	1

Chassis

160.	Altec Supplied Chassis	1
------	------------------------	---

<u>Item</u>	<u>Description</u>	<u>Qty</u>
161.	Chassis	1
162.	2021 Model Year	1
163.	International MV607	1
164.	4x2	1
165.	108 Clear CA (Round To Next Whole Number)	1
166.	Extended Cab (Larger Cab With Half-Length Rear Doors Or No Rear Doors)	1
167.	Low-Profile Hood	1
168.	Chassis Cab	1
169.	Set Back Axle	1
170.	Other Chassis Color	1
<p><u>Sales Text: NAV4015</u> Last Updated By: Joe Kedanis on 12-APR-2021 11:14</p>		
171.	Chassis Wheelbase Length - 202	1
172.	Cummins L9	1
173.	Diesel	1
174.	325 HP Engine Rating	1
175.	Allison 3000 RDS Automatic Transmission (Left and Right Side PTO Openings Only)	1
176.	GVWR 37,000 LBS	1
177.	14,000 LBS Front GAWR	1
178.	Spring Suspension	1
179.	23,000 LBS Rear GAWR	1
180.	Air Brakes	1
181.	Park Brake In Rear Wheels	1
182.	07BKS - International Exhaust (Right-Horizontal-Undercab-Vertical) (Cummins Engine Only) - Rear Wheel Drive Applications	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
183.	16XJV - International Dash Cutout for Switch Panel	1
184.	International - Disallow Regen while in PTO mode (13WEV)	1
185.	International Heavy Duty Tail Light Wiring (08HAB)	1
186.	International Transmission Dipstick Tube Enters Curbside of Transmission (13WGH)	1
187.	International Vertical Exhaust To Be Even With Top Of Cab (07WCM) and (07WAZ)	1
188.	International - Pre-Wire Chassis with Cab Pass-Thru (8HBE)	1
189.	50-State Emissions	1
190.	Clean Idle Certification	1
191.	15SXJ - International 50 Gallon Fuel Tank Non-Polished (Under Cab Left Hand)	1
192.	15WDG - International 7 Gallon DEF Tank (Under Cab Left Hand)	1
193.	120,000 Yield Strength (PSI)	1
194.	3 Chassis Batteries	1
195.	Other Battery Capacity (CCA)	1
<u>Sales Text: 650 CCA each battery</u>		
Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
196.	Battery Under Cab Left Hand	1
197.	Air Horn Under Cab	1
198.	AM/FM Radio	1
199.	Bluetooth	1
200.	12V DC Power Outlet	1
201.	Air Conditioning	1
202.	Cruise Control	1
203.	Keyless Entry	1
204.	Power Door Locks	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
205.	Power Windows	1
206.	Tilt Steering Wheel	1
207.	Tinted Windshield	1
208.	Other Interior Cab Options	1
<u>Sales Text:</u> USB charging port Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
209.	Block Heater	1
210.	Driver Controlled Locking Differential	1
211.	Fiberglass Tilting Hood	1
212.	Trailer Air Brake Package	1
213.	Other Exterior Cab Options	1
<u>Sales Text:</u> Two front tow hooks Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
214.	Air Ride Drivers Seat	1
<u>Sales Text:</u> Bucket seats with armrests Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
215.	Air Ride Passenger Seat	1
<u>Sales Text:</u> Bucket seats with armrests Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
216.	Other Seat Options	1
<u>Sales Text:</u> Rear bench seat Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
217.	Additional Chassis Option	1
<u>Sales Text:</u> Electronic road speed governor 65-70mph Last Updated By: Joe Kedanis on 23-JUL-2020 11:29		
218.	Additional Chassis Option	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
	<u>Sales Text:</u> Remote engine control for body builder Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
219.	Additional Chassis Option	1
	<u>Sales Text:</u> Antifreeze shall be Nitrite and Silicate free OAT coolant Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
220.	Additional Chassis Option	1
	<u>Sales Text:</u> Cold starting package. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
221.	Additional Chassis Option	1
	<u>Sales Text:</u> Heated fuel/water separator Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
222.	Additional Chassis Option	1
	<u>Sales Text:</u> Air dryer equipped with heater Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
223.	Additional Chassis Option	1
	<u>Sales Text:</u> 185 amp alternator Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
224.	Additional Chassis Option	1
	<u>Sales Text:</u> Battery disconnect Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
225.	Additional Chassis Option	1
	<u>Sales Text:</u> Two hood mounted blind spot mirrors. Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
226.	Additional Chassis Option	1
	<u>Sales Text:</u> Wheels painted white Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	
227.	Additional Chassis Option	1
	<u>Sales Text:</u> 3 sets of keys Last Updated By: Joe Kedanis on 23-JUL-2020 11:29	

<u>Item</u>	<u>Description</u>	<u>Qty</u>
<u>Additional Pricing</u>		
228.	Standard Altec Warranty: One (1) year parts warranty, one (1) year labor warranty, ninety (90) days warranty for travel charges, limited lifetime structural warranty	1
229.	Federal Excise Tax Item: If provided, Quote subtotal is an Estimate only. Final determined at invoicing.	1
<u>Miscellaneous</u>		
230.	Altec Provided Training	1

Total \$335,047.00

Altec Industries, Inc.

BY _____
Joe Kedanis , Technical Sales Representative

<u>Item Number</u>	<u>Description</u>
970329271-	Finish Paint Body Accessories Custom Color (Specify Color Code) NAV4015 Created By:Joe Kedanis on 15-DEC-2020 16:15
970693249-	Smooth Aluminum Tailshelf Floor Created By:Joe Kedanis on 15-DEC-2020 16:15
970693246-	Smooth Aluminum Floor (Preferred Option) Created By:Joe Kedanis on 15-DEC-2020 16:15
970079737-	Additional Unit And Hydraulic Accessory 4 Hydraulic reservoir guard with lid. Created By:Joe Kedanis on 15-DEC-2020 16:15
970650322-	Strobe Lights Wired Ignition Hot

Created By:Joe Kedanis on 15-DEC-2020 16:15

970650320-

Auxiliary Lighting Wired Ignition Hot

Created By:Joe Kedanis on 15-DEC-2020 16:15

970302382-

Hybrid Ready Option For Single Platform (Personnel Only)

Created By:Joe Kedanis on 14-JAN-2021 15:31

Notes: