EXHIBIT A

Page 1 of 3

LPA RX 851 WD Rev. 06/09

Ver. Date 09/12/2016 PID 95549

PARCEL 8-WD ARTERIAL STREET REHABILITATION - POLARIS PARKWAY ALL RIGHT, TITLE AND INTEREST IN FEE SIMPLE IN THE FOLLOWING DESCRIBED PROPERTY WITHOUT LIMITATION OF EXISTING ACCESS RIGHTS IN THE NAME AND FOR THE USE OF THE CITY OF COLUMBUS, DELAWARE COUNTY, OHIO

Grantor/Owner, for himself and his heirs, executors, administrators, successors and assigns, reserves all existing rights of ingress and egress to and from any residual area (as used herein, the expression "Grantor/Owner" includes the plural, and words in the masculine include the feminine or neuter).

[Surveyor's description of the premises follows]

Situated in the City of Columbus, County of Delaware, and State of Ohio, being in Farm Lot 18, Quarter Township 4, Township 3 North, Range 18 West of the United States Military District, and being a part of that 1.236 acre tract conveyed to NP Huntington, LLC, an Ohio Limited Liability Company, by Official Record 526, Page 1348, all references being to the Delaware County Recorder's Office, Delaware County, Ohio, and being bounded and more particularly described as follows:

Being a parcel of land lying on the south side of the centerline of existing right-of-way of Polaris Parkway, as shown and delineated upon the centerline plat with the right-of-way plans designated as Arterial Street Rehabilitation – Polaris Parkway prepared for the City of Columbus, Department of Public Services, by Carpenter Marty Transportation Inc., as recorded in Official Record Volume 1450, Page 927 (made a part hereof by reference), and being more particularly described as follows:

Beginning, for reference, at a 1" iron pipe found with a yellow cap stamped "CIVIL ENGR ASSOC." at a point of tangency in said centerline, said pin being Station 169+55.73 in said centerline;

Thence along said centerline the following two courses:

LPA RX 851 WD

- 1) North 46° 10' 37" East a distance of 502.91 feet to a point of curvature in said centerline, said point being Station 174+58.64 in said centerline;
- 2) With a curve to the right having a radius of 1432.39 feet, a central angle of 11° 35' 29", an arc length of 289.78 feet, a chord bearing North 51° 58' 21" East, and a chord distance of 289.29 feet to Station 177+48.42 in said centerline;

Thence South 32° 13' 54" East a distance of 50.00 feet to the Grantor's northeasterly corner, said point being 50.00 feet right of Station 177+48.42 in said centerline, said point also being the TRUE POINT OF BEGINNING of the parcel herein conveyed;

Thence along the Grantor's easterly line South 36° 05' 14" East a distance of 27.06 feet to a magnetic nail set in the proposed southerly right-of-way line of said Polaris Parkway, said nail being 77.00 feet right of Station 177+50.34 in said centerline;

Thence along said southerly line the following three courses:

- 1) With a curve to the left having a radius of 1355.39 feet, a central angle of 1° 39' 13", an arc length of 39.12 feet, a chord bearing South 57° 01' 06" West a distance of 39.12 feet to an iron pin set 77.00 feet right of Station 177+09.00 in said centerline;
- 2) North 33° 48' 31" West a distance of 7.00 feet to an iron pin set 70.00 feet right of Station 177+09.00 in said centerline;
- 3) With a curve to the left having a radius of 1362.39 feet, a central angle of 7° 13' 11", an arc length of 171.67 feet, a chord bearing South 52° 34' 54" West, and a chord distance of 171.56 feet to an iron pin set in the Grantor's westerly line, said pin being 70.00 feet right of Station 175+28.50 in said centerline;

LPA RX 851 WD Rev. 06/09

Thence along said westerly line North 43° 49' 23" West a distance of 20.02 feet to a 1" iron pipe found at the Grantor's northwesterly corner, said pipe being 50.00 feet right of Station 175+27.49 in said centerline;

Thence along the Grantor's northerly line, also being the existing southerly right-of-way line of said Polaris Parkway with a curve to the right having a radius of 1382.39 feet, a central angle of 8° 50' 13", an arc length of 213.21 feet, a chord bearing North 53° 20' 59" East, and a chord distance of 213.00 feet to the TRUE POINT OF BEGINNING, containing 0.104 acres, of which the present road occupies 0.000 acres.

The above described tract is located in Auditor's Parcel Number 318-442-02-027-004.

Grantor claims title by Official Record 526, Page 1348, Delaware County Recorder's Office.

This description is based on a survey performed for the City of Columbus in June of 2015 by Carpenter Marty Transportation Inc. This description was prepared and reviewed on June 30, 2016 by Kevin P. Carpenter, Registered Surveyor Number 8124.

The bearings found herein are based on the Ohio State Plane Coordinate System, North Zone, NAD 83 (2011). Bearings shown heron are based on true north observed by Carpenter Marty Transportation, using a Leica GNSS Viva CS15/GS15 receiver. Based on this the bearing of Interstate 71 is North 3° 32' 22" East.

Monuments referred to as iron pins set are ³/₄" x 30" topped by a 2" diameter aluminum cap stamped "CITY OF COLUMBUS R/W, P.S. 8124". Right of way monuments called for as set herein shall be set upon completion of the acquisition process.