LPA RX 851 WD

Page 1 of 3 Rev. 06/09

Ver. Date 09/12/2016 PID 95549

PARCEL 17-WD2 ARTERIAL STREET REHABILITATION - POLARIS PARKWAY ALL RIGHT, TITLE AND INTEREST IN FEE SIMPLE IN THE FOLLOWING DESCRIBED PROPERTY WITHOUT LIMITATION OF EXISTING ACCESS RIGHTS IN THE NAME AND FOR THE USE OF THE CITY OF COLUMBUS, DELAWARE COUNTY, OHIO

Grantor/Owner, for himself and his heirs, executors, administrators, successors and assigns, reserves all existing rights of ingress and egress to and from any residual area (as used herein, the expression "Grantor/Owner" includes the plural, and words in the masculine include the feminine or neuter).

[Surveyor's description of the premises follows]

Situated in the City of Columbus, County of Delaware, and State of Ohio, being in Farm Lot 19, Quarter Township 4, Township 3 North, Range 18 West of the United States Military District, and being a part of that 3.929 acre tract conveyed to the Ohio District Council, Inc. of the Assemblies of God, by Official Record 687, Page 1386, all references being to the Delaware County Recorder's Office, Delaware County, Ohio, and being bounded and more particularly described as follows:

Being a parcel of land lying on the west side of the centerline of existing right-of-way of Orion Place and Worthington Road, as shown and delineated upon the centerline plat with the right-ofway plans designated as Arterial Street Rehabilitation – Polaris Parkway prepared for the City of Columbus, Department of Public Services, by Carpenter Marty Transportation Inc., as recorded in Official Record Volume 1450, Page 927 (made a part hereof by reference), and being more particularly described as follows:

Beginning, for reference, at a 1" iron pipe found with a yellow cap stamped "CIVIL ENGR ASSOC." at a point of tangency in the centerline of Polaris Parkway, said pin being Station 169+55.73 in said centerline;

LPA RX 851 WD Rev. 06/09

Thence along said centerline with a curve to the right having a radius of 1,762.95 feet, a central angle of 18° 03' 40", an arc length of 555.73 feet, a chord bearing South 55° 12' 27" West, and a chord distance of 553.43 feet to the existing intersection of said line with the existing centerline of Orion Place, said point being Station 164+00.00 in said centerline of Polaris Parkway;

Thence along the centerline of said Orion Place/Worthington Road the following four courses:

- 1) South 25° 45' 43" East a distance of 212.81 feet to a point of curvature, said point being Station 2+12.81 in said centerline;
- 2) With a curve to the right having a radius of 900.00 feet, a central angle of 18° 09' 53", an arc length of 285.33 feet, a chord bearing South 16° 40' 47" East, and a chord distance of 284.14 feet to a point of tangency, said point being Station 4+98.14 in said centerline;
- 3) South 7° 35' 35" East a distance of 499.75 feet to a point of curvature, said point being Station 9+97.89 in said centerline;
- 4) With a curve to the right having a radius of 446.66 feet, a central angle of 29° 07' 58", an arc length of 227.11 feet, a chord bearing South 6° 58' 24" West, and a chord distance of 224.67 feet Station 12+25.00 in said centerline;

Thence North 68° 27' 37" West a distance of 40.00 feet to an iron pin set in the existing westerly right-of-way line of said Worthington Road, said pin being 40.00 feet right of Station 12+25.00 in said centerline, said pin also being the TRUE POINT OF BEGINNING of the parcel herein conveyed;

Thence along said westerly line, also being the Grantor's easterly line, with a curve to the right having a radius of 406.66 feet, a central angle of 4° 12' 20", an arc length of 29.85 feet, a chord bearing South 23° 38' 35" West, and a chord distance of 29.84 feet to an 1" iron pipe found with

LPA RX 851 WD

a yellow cap stamped "BIRD & BULL INC." at the Grantor's southeasterly corner, said pipe being 40.00 feet right of Station 12+57.79 in said centerline;

Thence along the Grantor's southerly line South 80° 27' 39" West a distance of 8.36 feet to an iron pin set in the proposed westerly right-of-way line of said Worthington Road, said pin being 46.80 feet right of Station 12+63.19 in said centerline;

Thence along said westerly line North 35° 08' 00" East a distance of 35.13 feet to the TRUE POINT OF BEGINNING, containing 0.003 acres, of which the present road occupies 0.000 acres.

The above described tract is located in Auditor's Parcel Number 318-443-02-009-001.

Grantor claims title by Official Record 687, Page 1386, Delaware County Recorder's Office.

This description is based on a survey performed for the City of Columbus in June of 2015 by Carpenter Marty Transportation Inc. This description was prepared and reviewed on June 30, 2016 by Kevin P. Carpenter, Registered Surveyor Number 8124.

The bearings found herein are based on the Ohio State Plane Coordinate System, North Zone, NAD 83 (2011). Bearings shown heron are based on true north observed by Carpenter Marty Transportation, using a Leica GNSS Viva CS15/GS15 receiver. Based on this the bearing of Interstate 71 is North 3° 32' 22" East.

Monuments referred to as iron pins set are ³/₄" x 30" topped by a 2" diameter aluminum cap stamped "CITY OF COLUMBUS R/W, P.S. 8124". Right of way monuments called for as set herein shall be set upon completion of the acquisition process.