CONFLUENCE VILLAGE

Situated in the State of Ohio, County of Franklin, City of Columbus, and in Half Sections 8 and 9, Township 5, Range 22, Refugee Lands, containing 28.631 acres of land, more or less, said 28.631 acres being comprised of a resubdivision of the subdivision entitled "W.A. Neil's Waterworks Addition", of record in Plat Book 3, Page 33, Lot F of the subdivision entitled "W.A. Neil's Penitentiary Farm", of record in Plat Book 5, Page 44, and Lots 13,14, 17, 18 and 21 of the subdivision entitled "Brecount, Conover and Smith's Northwest Addition," of record in Plat Book 1, Page 250, said resubdivided areas being conveyed to **WEST END DEVELOPMENT**, **LLC** by deeds of record in Instrument Numbers 201910310145389 and 201910310145390, Recorder's Office, Franklin County, Ohio, and those portions of Broadbelt (Brodbelt) Alley, Michigan Avenue, Hocking Street, Nationwide Boulevard and those unnamed alleys vacated by City of Columbus Ordinance Numbers 23-31, 139-33, 1118-2010, 37065, 2093-2019 and

The undersigned, WEST END DEVELOPMENT, LLC, A Delaware limited liability company by DAVID A. JENKINS, Authorized Officer, owner of the lands platted herein, duly authorized in the premises, does hereby certify that this plat correctly represents its "CONFLUENCE VILLAGE", a subdivision containing Lots numbered 1 to 5, both inclusive, does hereby accept this plat of same and dedicates to public use, as such, all of Street A, Street B, Street C and Street D shown hereon and not heretofore

Easements are hereby reserved in, over and under areas designated on this plat as "Easement" or "Sidewalk Easement". Each of the aforementioned designated easements permit the construction, operation and maintenance of all public and quasi public utilities, above, beneath and on the surface of the ground, and where necessary, for the construction, operation and maintenance of service connections to all adjacent lots and lands and for storm water drainage. Within those areas designated "Sidewalk Easement" on this plat, an additional easement is hereby reserved for the construction and maintenance of a sidewalk for use by the public. Within those areas designated "Access Easement" on this plat, an additional easement is reserved for vehicular turnaround use by

In Witness	Whereof, DAVI	D A. JENKINS,	Authorized Officer	of WEST EN
DEVELOPMENT	Γ, LLC has hereu	nto set his hand th	isday of	, 20


Signed and Acknowledged In the presence of	WEST END DEVELOPMENT, LL
	By


STATE OF OHIO **COUNTY OF CUYAHOGA ss:**

Before me, a Notary Public in and for said State, personally appeared **DAVID A. JENKINS**, Authorized Officer of **WEST END DEVELOPMENT**, **LLC** who acknowledged the signing of the foregoing instrument to be his voluntary act and deed and the voluntary act and deed of said WEST END DEVELOPMENT, LLC for the uses and purposes expressed herein.

In Witness Thereof, I have day of, 20	-	hand and affix	xed my official seal this	3
My commission expires	—			

State of Ohio





LOCATION MAP AND BACKGROUND DRAWING

NOT TO SCALE

SURVEY DATA:

BASIS OF BEARINGS: The bearings shown hereon are based on the portion of the northerly right of way line of Nationwide Boulevard, having a bearing of North 82°21' 25" East, as per Ohio State Plane Coordinate System, South Zone NAD83 (1986

SOURCE OF DATA: The sources of recorded survey data referenced in the plan and text of this plat are the records of the Recorder's Office, Franklin County, Ohio.

IRON PINS: Iron pins, where indicated hereon, unless otherwise noted, are to be set and are iron pipes thirteen sixteenths inch inside diameter, thirty inches long with a plastic plug placed in the top end bearing the initials EMHT INC.

PERMANENT MARKERS: Permanent markers, where indicated hereon in the public street centerline, are to be 8-inch long mag spikes. Mag spikes are to be set to monument the points indicated, are to be set after the construction/installation of the street pavement, and are to be set with the top end one-fourth inch below the top of the pavement. Once installed, the top of the pin shall be marked (punched) to record the actual location of the point. Permanent markers, where indicated hereon in positions other than in the public street centerline, are to be one-inch diameter, thirty-inches long, solid iron pins, are to be set to monument the points indicated, are to be set with the top end flush with the surface of the ground, and then capped with an aluminum cap stamped EMHT INC. Once installed, the top of the cap shall be marked (punched) to record the actual location of the point.

SURVEYED & PLATTED



We do hereby certify that we have surveyed the above premises, prepared the attached plat, and that said plat is correct. All dimensions are in feet and decimal parts thereof.

O = Iron Pin (See Survey Data)

= MAG Spike to be set

© = Permanent Marker (See Survey Data)

■ = 4" Steel Fence Post found

 \otimes = Chiseled X found

Professional Surveyor No. 7865